



COUNTY OF SAN JOAQUIN

DEPARTMENT OF PUBLIC WORKS
P.O. BOX 1810-1810 E. HAZELTON AVENUE
STOCKTON, CALIFORNIA 95201
(209) 468-3000
FAX # (209) 468-9324

Permit No: **PS-1600944**
Date Issued: 04/07/2016
Start Date: 04/07/2016
Exp. Date: 05/15/2016
Project No: PWP730079
Quad: SE

UE/CR/PM NO:9660307

ENCROACHMENT PERMIT

To: AT & T - FRESNO
5555 E. OLIVE RM#300III
FRESNO, CA 93727

Encroachment Type:

TCP			
-----	--	--	--

Location:

S/S E RIVER RD 2601' MCHENRY AVE

In compliance with your request of 04/07/2016, permission is hereby granted to do work in County right-of-way as shown on attached application and subject to all the terms, conditions and restrictions written below or printed as general or special provisions on any part of this form. See reverse side and attached sheet, if any.

Trench excavations for service connections will not be permitted within ten feet (10') of pavement centerline unless otherwise approved by the Director. Surface of trench patches shall match in kind and be smooth and even with that of abutting surface. Special attention shall be given to depth of utilities through roadside area in anticipation of future drainage facilities, road profile and/or frontage development. All underground utility facilities are to be established and accurately dimensioned on sketches from surveyed centerline of road right of way, or from right of way (border) lines.

~~Permittee shall call the Department of Public Works, Field Engineering Division (Permit Inspections) at (209)953-7421 at least forty-eight hours prior to beginning any work within the County right of way.~~ All work performed under this permit shall conform to the rules and regulations pertaining to safety established by the California Division of Industrial Safety and Cal-OSHA.

The jobsite shall be kept in a safe condition at all times by the daily removal of any excess dirt or debris which might be a hazard to either pedestrian or automobile traffic. All necessary traffic convenience and warning devices and personnel shall be provided, placed and maintained by and at the sole expense of the Permittee in accordance with the latest edition of the CALTRANS Manual of Traffic Control.

After completion of the work permitted herein, all debris, lumber, barricades, or any excess material shall be removed and the jobsite left in a neat workmanlike manner. ~~Immediately following completion of construction permitted herein, Permittee shall fill-out and mail notice of completion (see attached post card) provided by Grantor.~~

Special Comments:

Traffic Control Per MUTCD

FORMS:

SS/WW, R-29		
-------------	--	--

Est. Permit Fee: \$436.00

KRIS BALAJI, Director
Department of Public Works

- WHITE -Permittee
- GOLDENROD -PWD Central File
- YELLOW -Field Inspection
- PINK -Permit Section

By: 
Permit Section

ENCROACHMENT PERMIT GENERAL PROVISIONS

13-1.

1. This permit is issued under and subject to all laws and ordinances of agencies governing the encroachment herein permitted. See the following references:

STREETS AND HIGHWAYS CODE

1. Division 1, Chapter 3
2. Division 2, Chapter 2, Section 942
3. Division 2, Chapter 4, Section 1126
4. Division 2, Chapter 5.5 and Chapter 6

SAN JOAQUIN COUNTY ORDINANCES NUMBERED: 324, 441, 648, 662, 672, 695, 700, 860, 892, 3359, and 3675.

2. It is understood and agreed by the Permittee that the performance of any work under this permit shall constitute an acceptance of all the provisions contained herein and failure on the Permittee's part to comply with any provision will be cause for revocation of this permit. Except as otherwise provided for public agencies and franchise holders, this permit is revocable on five days notice.
3. All work shall be done subject to the supervision of and the satisfaction of the grantor. The Permittee shall at all times during the progress of the work keep the County Highway in as neat and clean condition as is possible and upon completion of the work authorized herein, shall leave the County Highway in a thoroughly neat, clean and usable condition.
4. The Permittee also agrees by the acceptance of this permit to properly maintain any encroachment structure placed by the Permittee on any part of the County Highway and to immediately repair any damage to any portion of the highway, which occurs as a result of the maintenance of the said encroachment structure, until such time as the Permittee may be relieved of the responsibility for such maintenance by the County of San Joaquin.
5. The Permittee also agrees by the acceptance of this permit to make, at its own expense, such repairs as may be deemed necessary by the County Department of Public Works.
6. It is further agreed by the Permittee that whenever construction, reconstruction or maintenance work upon the highway is necessary, the installation provided for herein shall, upon request of the County Department of Public Works, be immediately moved or removed by and at the sole expense of the Permittee.
7. No material used for fill or backfill in the construction of the encroachment shall be borrowed or taken from within the County right of way.
8. All work shall be planned and carried out with as little inconvenience as possible to the traveling public. No material shall be stacked within eight feet (8') of the edge of the pavement or traveled way unless otherwise provided herein. Adequate provision shall be made for the protection of the traveling public. Traffic control standards shall be utilized including barricades; approved signs and lights; and flagmen, as required by the particular work in progress.
9. The Permittee, by the acceptance of this permit, shall assume full responsibility for all liability for personal injury or damage to property which may arise out of the work herein permitted or which may arise out of the failure of the part of the Permittee to properly perform the work provided under this permit. In the event any claim of such liability is made against the County of San Joaquin or any department, official or employee thereof, the Permittee shall defend, indemnify, and hold each of them harmless for such claim.
10. All backfill material is to be moistened as necessary and thoroughly compacted with mechanical means. If required by the County Director of Public Works, such backfill shall consist of gravel or crushed rock. The Permittee shall maintain the surface over structures placed hereunder as may be necessary to insure the return of the roadway to a completely stable condition and until relieved of such responsibility by the County Department of Public Works. Wherever a gravel, crushed rock or asphalt surface is removed or damaged in the course of work related to the permitted encroachment, such material shall either be separately stored and replaced in the roadway as nearly as possible in its original state or shall be replaced in kind, and the roadway shall be left in at least as good a condition as it was before the commencement of operations of placing the encroachment structure.
11. Whenever it becomes necessary to secure permission from abutting property owners for the proposed work, such authority must be secured by the Permittee prior to starting work.
12. The current and future safety and convenience of the traveling public shall be given every consideration in the location and methods of construction utilized.
13. The Permittee is responsible for the preservation of survey monuments located within the area of work herein permitted. Prior to the start of construction, survey monuments that potentially may be disturbed shall be located and referenced by a Licensed Land Surveyor, and a Corner Record filed with the County Surveyor. Any Survey Monuments disturbed during the course of construction shall be reestablished by a Licensed Land Surveyor and another Corner Record filed with the County Surveyor. (Land Surveyors' Act Section 8771)
14. Prior to any excavation, the Permittee shall notify USA North (Underground Service Alert of Northern California and Nevada) at 811 or 800-227-2600 forty-eight (48) hours in advance.

APPLICATION FOR ENCROACHMENT PERMIT

2016 MAR 14 PM 1:53

DEPT OF PUBLIC WORKS

PLEASE PRINT:

Date 02/29/2016

To: San Joaquin County
Department of Public Works.

AT&T / Sherry Parks (Permits Desk)
(Applicant Name)

5555 E. Olive Ave
(Mailing Address)

Fresno, CA 93727
(City, State, Zip Code)

(559) 454-4900 g26977@att.com
(Area Code - Telephone Number)

OFFICE USE ONLY			
JOB #	<u>730079</u>	REF #	
APN		CR #	
EXP. DATE	<u>5-15-16</u>		
VALID	<u>4-7-16</u> TO <u>5-15-16</u>	DRIVEWAYS:	
STREET	<u>River Rd</u>	*	
AREA	<u>Escalon</u> QUAD <u>SE</u>	*	
TYPE	<u>Trench</u>	*	
FORMS	<u>SSW/R 29</u>		
NOTES			

Sketch (Detailed plans may be submitted)

Please see the attached drawings.

The undersigned hereby applies for permission to excavate, construct and/or otherwise encroach on County Highway Right-of-Way on the South side of E River Rd approximately 2601 feet/mile feet of McHenry Ave, by performing the following work (description of work): Place 2'- 1-4" duct via trench, Place (1) 30"x48" new splice box at the property line. Traffic control plan is in place on E River Rd for trenching and on Mc Henry and East River road for aerial access. Please see the attached drawings.

Work will commence on or about 3/30/2016 for approximately 30 days.



I, the undersigned, certify that I am the owner of the respective property, or am qualified to represent the owner and agree to do the work described above in accordance with the rules and regulations of San Joaquin County and subject to inspection and approval.

[Signature]
Signature of Applicant - Title

3/11/16
Date

CONSTRUCTION NOTES

- ① PL. 2" 1-4" DUCT
PTS 77 OR EQUIV.
PM 1 DU 2'
VIA TRENCH
- ② PL. 30"x48" SB @ PROPERTY LINE



ISSUE	DATE
1	2/24/16

LEGEND

- POLE
- FACE OF CURB
- PROPOSED CONDUIT
- PROPERTY LINE
- ⊕ CENTERLINE
- ⊖ BACK OF SIDEWALK
- ⊞ STOP SIGN
- ▭ CONCRETE SIDEWALK
- ⊔ EDGE OF PAVEMENT


SAFETY NOTE
 WORK AREA WILL INCLUDE LANE CLOSURE ON ROAD WITH VERY HIGH TRAFFIC VOLUME. PLEASE PROVIDE COMPLETE WORK AREA PROTECTION.

USA DIG
 #1-800-227-2800
 BEFORE DIGGING


COUNTY OF SAN JOAQUIN
 START DATE : FEB. 24, 2016
 END DATE : APR. 24, 2016

M.O.P REQUIRED CATEGORY - 3
 FOLLOW PROCEDURES AS DETAILED IN NORTHERN SECTOR PLAN FOR PROTECTION OF UNDERGROUND AND BURIED CABLE M.O.P. DATED

- GENERAL NOTES:**
- CONTRACTOR SHALL REQUEST LOCATION OF UNDERGROUND FACILITIES BY USA
 - CONTRACTOR WILL COMPLY WITH ALL SAN JOAQUIN COUNTY REGULATIONS FOR SPLICE PIT & SURFACE COMPACTION
 - CONTRACTOR WILL RETURN WORK AREA BACK TO ORIGINAL OR BETTER CONDITION PRIOR TO START OF WORK
 - MAINTAIN 36" MINIMUM COVER



TYPICAL TRENCH DETAIL




EXCAVATION DATA			
OWNER	ASPHALT	DIRT	CONCRETE
COUNTY OF SAN JOAQUIN	—	(SB) 4'X3'=12 SQ FT 2'X1'=2 SQ FT	—


GEO / CD SBES
EXCHANGED FRNCAII
ENGL ELLI SMITH
TEL 619-786-2826 ENGLARC VOIKDCABR
TYPE OF CONST.
UG CONDUIT PLACEMENT
RD / EST NO. 5660307
DWG 1 OF 1 P

Consulting, LLC
 1846 W. Orangewood Ave., Suite # 200,
 Orange, CA 92668
 (949) 250-0004 / FAX (949) 250-0008

SIGN LEGEND



LEGEND



JOB LOCATION
E. RIVER RD

WORK HOURS
FROM: TO:
BRENAN RD MCHENRY AVE

PERMIT NO.

WORK TO BE DONE
TRENCHING

START DATE **END DATE**

POSTED SPEED LIMIT	APPROACH SPEED	TAPER LENGTH	SPACING OF CONES	SIGN SPACING
55 MPH	55 MPH	220 FT.	55 FT.	500 FT.

PERMIT WORK EXTENSIONS MUST BE OBTAINED BY THE END OF PERMIT DATE

GENERAL NOTES:
FOR HOURS OF DARKNESS, CHANGE CONES TO VERTICAL BARRICADES WITH STEADY BURN LIGHTS.
NOTHING CONTAINED ON THIS DRAWING SHALL PREVENT LOCAL JURISDICTIONS FROM MODIFICATIONS, CHANGES, OR ADOPTING NEW SPECIFICATIONS DEEMED NECESSARY.
CRITERIA FOR POSITION, LOCATION, AND USE OF TRAFFIC CONTROL DEVICES IS SOLELY FOR THE PURPOSE OF GUIDANCE TO ASSIST IN THE SET UP OF THE TRAFFIC CONTROL PLANS.

REQUIREMENTS:

- THE CONTRACTOR IS RESPONSIBLE FOR PROMPTLY RESTORING THE ROAD BACK TO SATISFACTORY CONDITION WHICH INCLUDES, BUT IS NOT LIMITED TO, PAVING, STRIPPING, MARKINGS, SIGNING, AND LOOP DETECTION. ALL PLANS SHALL BE IN ACCORDANCE WITH 2014 CA MUTCD.
- THE AGENCY RESERVES THE RIGHT TO OBSERVE THESE TRAFFIC CONTROL PLANS IN OPERATION AND TO MAKE CHANGES AS FIELD CONDITIONS WARRANT.
- TRENCHES SHALL BE BACK-FILLED OR STEEL-PLATED DURING NON-WORK HOURS. STEEL PLATES SHALL HAVE AN ASPHALT RAMP ON ALL EDGES, SECURELY SUPPORTED SO THEY WON'T ROCK AND A SIGN POSTED NEAR THE PLATES IDENTIFYING THE CONTRACTORS NAME AND 24 HOUR EMERGENCY TELEPHONE NUMBER. ALL DIRT, DUST, AND DEBRIS SHALL BE REMOVED FROM THE STREET AT THE END OF EACH DAY AND AT THE END OF THE JOB. THE STREET SHALL BE KEPT IN A DRIVABLE CONDITION AT ALL TIMES.
- ANY WORK THAT CREATES AN UNLIE SAFETY RISK OR THAT CREATES SEVERE CONGESTION WILL BE SHUT DOWN BY THE AGENCY.
- A COPY OF ALL TRAFFIC REQUIREMENTS AND TRAFFIC CONTROL PLANS ISSUED BY THE AGENCY MUST BE KEPT ON THE JOB SITE.
- APPROVAL OF THIS PLAN DOES NOT CONSTITUTE AN OFFICIAL PERMIT. CONTACT THE AGENCY FOR INFORMATION ON OBTAINING A PERMIT.
- ALL TRAVEL LANES WILL TYPICALLY BE A MINIMUM OF 12 FEET WIDE, 14 FEET IF ADJACENT TO BIKE LANES, UNLESS OTHERWISE SPECIFICALLY APPROVED BY THE AGENCY.
- FLASHING ARROW BOARDS AS REQUIRED BY THE AGENCY.
- WARNING (W) SERIES SIGNS USED IN WORK ZONES SHALL BE BLACK ON AN ORANGE BACKGROUND.
- CONES AND PYLONS SHALL HAVE YELLOW REFLECTORIZED SLEEVES WHEN PLACED ALONG THE CENTERLINE AND WHITE REFLECTORIZED SLEEVES ALONG THE OUTSIDE SHOULDER.
- IF PARKING IS ALLOWED IN THE ADVANCE WORKING AREA, ADVANCE WARNING SIGNS SHALL BE MOUNTED ON HIGH LEVEL DEVICES.
- THE CONTRACTOR SHALL POST TOW-AWAY/NO PARKING SIGNS SEVENTY-TWO (72) HOURS IN ADVANCE, WITH DAY OF WEEK, DATE, AND WORK HOURS NOTED, AND SHALL BAG PARKING METERS (WHERE APPLICABLE).
- OPEN CUT WORK SHALL BE DONE IN 3 PHASES.
- WORKERS SHALL WEAR HARD HATS AND ORANGE VESTS AT ALL TIMES.
- COUNTY TRANSIT DISTRICT SHALL BE NOTIFIED (3) WORKING DAYS PRIOR TO ANY WORK THAT AFFECTS BUS STOPS.
- CONSTRUCTION SIGNS SHALL NOT OBSTRUCT SIGHT VISIBILITY AT DRIVEWAYS.
- CONTRACTOR SHALL NOTIFY ALL LOCAL BUSINESS OWNERS/OCCUPANTS TWO DAYS IN ADVANCE PRIOR TO ANY CONSTRUCTION ADJACENT TO BUSINESSES.

TABLE 8C-1 2014 CALIFORNIA MUTCD - SUGGESTED MINIMUM ADVANCE WARNING SIGN SPACINGS*

ROAD TYPE	DISTANCE BETWEEN SIGNS**		
	A	B	C
Urban arterial with median	100 FEET	120 FEET	150 FEET
Urban arterial without median	200 FEET	250 FEET	300 FEET
Urban collector with median	350 FEET	450 FEET	550 FEET
Urban collector without median	500 FEET	600 FEET	700 FEET
Suburban arterial	1000 FEET	1200 FEET	1500 FEET

** THE COLUMN HEADINGS A, B, AND C ARE THE DIMENSIONS SHOWN IN FIGURES 8A-1 THROUGH 8A-6. THE DIMENSION IS THE DISTANCE FROM THE TRANSITION OR POINT OF ORIGIN TO FIRST SIGN. THE B DIMENSION IS THE DISTANCE BETWEEN THE FIRST AND SECOND SIGNS. THE C DIMENSION IS THE DISTANCE BETWEEN THE SECOND AND THIRD SIGNS. (THE THIRD SIGN IS THE FIRST ONE IN THE THREE-SIGN SERIES ENCOUNTERED IN A CORNER APPROACHING A TJC CORNER.)

TABLE 8C-2 2014 CALIFORNIA MUTCD - STOPPING SIGHT DISTANCE AS A FUNCTION OF SPEED*

SPEED (MPH)	DISTANCE (FT)
15	115
20	155
25	205
30	265
35	335
40	415
45	505
50	605
55	725
60	865
65	1025
70	1205
75	1405
80	1625
85	1875
90	2155
95	2465
100	2805

* POSTED SPEED, OFF-PEAK ESTIMATED SPEED, ROAD TO WORK, STANDING OR THE ANTICIPATED OPERATED SPEED IN MPH (MPS)

TABLE 8C-3 2014 CALIFORNIA MUTCD - TAPER LENGTH CRITERIA FOR TEMPORARY TRAFFIC CONTROL ZONE*

TYPE OF TAPER	TAPER LENGTH (FT)
CONCRETE	25 FEET
WOOD	25 FEET
PORTLAND CEMENT	25 FEET
ASPHALT	25 FEET
GRAVEL	25 FEET
OTHER	25 FEET

TABLE 8C-4 2014 CALIFORNIA MUTCD - FORMULAS FOR DETERMINING TAPER LENGTH*

W	WIDTH OF OFFSET IN METERS (FEET)
S	POSTED SPEED LIMIT, OR OFF-PEAK ESTIMATED SPEED FROM TO WORK STARTING, OR THE ANTICIPATED OPERATED SPEED IN MPH (MPS)

W = TAPER LENGTH IN METERS (FEET)
S = WIDTH OF OFFSET IN METERS (FEET)
S = POSTED SPEED LIMIT, OR OFF-PEAK ESTIMATED SPEED FROM TO WORK STARTING, OR THE ANTICIPATED OPERATED SPEED IN MPH (MPS)

SAN JOAQUIN COUNTY TRAFFIC CONTROL PLAN


JOB NUMBER **9660307**
SCALE: NONE
PAGE: 1 OF 2

PLANS ACCEPTED BY: _____ DATE _____
R.C.E. _____
E.P. DATE _____


PLANS PREPARED BY:
NAME: **MIKE MATHERNE**
PHONE: **855-405-6916**
DATE: **2-25-16**



SIGN LEGEND



LEGEND



REQUIREMENTS:

1. THE CONTRACTOR IS RESPONSIBLE FOR PROMPTLY RESTORING THE ROAD BACK TO SATISFACTORY CONDITION WHICH INCLUDES, BUT IS NOT LIMITED TO, PAVING, STRIPPING, MARKINGS, SIGNING, AND LOOP DETECTION. ALL PLANS SHALL BE IN ACCORDANCE WITH 2014 CA MUTCD.
2. THE AGENCY RESERVES THE RIGHT TO OBSERVE THESE TRAFFIC CONTROL PLANS IN OPERATION AND TO MAKE CHANGES AS FIELD CONDITIONS WARRANT.
3. TRENCHES SHALL BE BACK-FILLED OR STEEL-PLATED DURING NON-WORK HOURS. STEEL PLATES SHALL HAVE AN ASPHALT RAMP ON ALL EDGES, SECURELY SUPPORTED SO THEY WON'T ROCK AND A SIGN POSTED NEAR THE PLATES IDENTIFYING THE CONTRACTOR'S NAME AND 24 HOUR EMERGENCY TELEPHONE NUMBER. ALL DIRT, DUST, AND DEBRIS SHALL BE REMOVED FROM THE STREET AT THE END OF EACH DAY AND AT THE END OF THE JOB. THE STREET SHALL BE KEPT IN A DRIVABLE CONDITION AT ALL TIMES.
4. ANY WORK THAT CREATES AN UNQUE SAFETY RISK OR THAT CREATES SEVERE CONGESTION WILL BE SHUT DOWN BY THE AGENCY.
5. A COPY OF ALL TRAFFIC REQUIREMENTS AND TRAFFIC CONTROL PLANS ISSUED BY THE AGENCY MUST BE KEPT ON THE JOB SITE.
6. APPROVAL OF THIS PLAN DOES NOT CONSTITUTE AN OFFICIAL PERMIT. CONTACT THE AGENCY FOR INFORMATION ON OBTAINING A PERMIT.
7. ALL TRAVEL LANES WILL TYPICALLY BE A MINIMUM OF 12 FEET WIDE, 14 FEET IF ADJACENT TO BIKE LANES, UNLESS OTHERWISE SPECIFICALLY APPROVED BY THE AGENCY.
8. FLASHING ARROW BOARDS AS REQUIRED BY THE AGENCY.
9. WARNING (W) SERIES SIGNS USED IN WORK ZONES SHALL BE BLACK ON AN ORANGE BACKGROUND.
10. CONES AND PYLONS SHALL HAVE YELLOW REFLECTORIZED SLEEVES WHEN PLACED ALONG THE CENTERLINE AND WHITE REFLECTORIZED SLEEVES ALONG THE OUTSIDE SHOULDER.
11. IF PARKING IS ALLOWED IN THE ADVANCE WORKING AREA, ADVANCE WARNING SIGNS SHALL BE MOUNTED ON HIGH LEVEL DEVICES.
12. THE CONTRACTOR SHALL POST TOW-AWAY/NO PARKING SIGNS SEVENTY-TWO (72) HOURS IN ADVANCE, WITH DAY OF WEEK, DATE, AND WORK HOURS NOTED, AND SHALL BAG PARKING METERS (WHERE APPLICABLE).
13. OPEN CUT WORK SHALL BE DONE IN ___ PHASES.
14. WORKERS SHALL WEAR HARD HATS AND ORANGE VESTS AT ALL TIMES.
15. COUNTY TRANSIT DISTRICT SHALL BE NOTIFIED (5) WORKING DAYS PRIOR TO ANY WORK THAT AFFECTS BUS STOPS.
16. CONSTRUCTION SIGNS SHALL NOT OBSTRUCT SIGHT VISIBILITY AT DRIVEWAYS.
17. CONTRACTOR SHALL NOTIFY ALL LOCAL BUSINESS OWNERS/OCCUPANTS TWO DAYS IN ADVANCE PRIOR TO ANY CONSTRUCTION ADJACENT TO BUSINESSES.

JOB LOCATION
McHENRY AVE, E. RIVER RD
 BEGIN CROSS STREET
CLOUGH RD

WORK HOURS
 FROM: _____ TO: _____
 END CROSS STREET
BRENNAN RD

PERMIT NO. _____

WORK TO BE DONE
AERIAL

START DATE _____ END DATE _____

PERMIT WORK EXTENSIONS MUST BE OBTAINED BY THE END OF PERMIT DATE

POSTED SPEED LIMIT	APPROACH SPEED	TAPER LENGTH	SPACING OF CONES	SIGN SPACING
55 MPH	55 MPH	220 FT.	55 FT.	500 FT.

GENERAL NOTES:
 FOR HOURS OF DARKNESS, CHANGE CONES TO VERTICAL BARRICADES WITH STEADY BURN LIGHTS.
 NOTHING CONTAINED ON THIS DRAWING SHALL PREVENT LOCAL JURISDICTIONS FROM MODIFYING, CHANGING, OR ADOPTING NEW SPECIFICATIONS DEEMED NECESSARY.
 CRITERIA FOR POSITION, LOCATION, AND USE OF TRAFFIC CONTROL DEVICES IS SOLELY FOR THE PURPOSE OF GUIDANCE TO ASSIST IN THE SET UP OF THE TRAFFIC CONTROL PLANS.

TABLE 6C-1 2014 CALIFORNIA MUTCD - SUGGESTED MINIMUM ADVANCE WARNING SIGN SPACING

ROAD TYPE	DISTANCE BETWEEN SIGNS**		
	A	B	C
Urban/Urban-Divided (with or without turn lanes)	150 FEET	100 FEET	100 FEET
Urban/Urban-Divided (with or without turn lanes) with 100 ft. or more	250 FEET	250 FEET	250 FEET
Urban/Urban-Divided (with or without turn lanes) with 100 ft. or more	350 FEET	250 FEET	250 FEET
Urban/Urban-Divided (with or without turn lanes) with 100 ft. or more	500 FEET	500 FEET	500 FEET
Urban/Urban-Divided (with or without turn lanes) with 100 ft. or more	1000 FEET	1000 FEET	1000 FEET

TABLE 6C-2 2014 CALIFORNIA MUTCD - STOPPING SIGHT DISTANCE AS A FUNCTION OF SPEED

SPEED (MPH)	DISTANCE (FT)
20	115
25	155
30	200
35	250
40	300
45	350
50	400
55	450
60	500
65	550
70	600

TABLE 6C-3 2014 CALIFORNIA MUTCD - TAPER LENGTH CRITERIA FOR TEMPORARY TRAFFIC CONTROL ZONE

TYPE OF TAPER	TAPER LENGTH (L) AT SPEED (S)
WINDING TAPER	AT LEAST L
DIAGONAL TAPER	AT LEAST 0.5L
SHOULDER TAPER	AT LEAST 0.5L
FLY BAR TAPER	AT LEAST 0.5L
DOWNSTREAM TAPER	20 ft. MINIMUM PER LANE

TABLE 6C-4 2014 CALIFORNIA MUTCD - FORMULAS FOR DETERMINING TAPER LENGTH

TYPE OF TAPER	FORMULA
WINDING TAPER	$L = \frac{S^2}{10}$
DIAGONAL TAPER	$L = \frac{S^2}{10}$
SHOULDER TAPER	$L = \frac{S^2}{10}$
FLY BAR TAPER	$L = \frac{S^2}{10}$
DOWNSTREAM TAPER	$L = \frac{S^2}{10}$

SAN JOAQUIN COUNTY TRAFFIC CONTROL PLAN


PLANS ACCEPTED BY: _____ DATE _____
 R.C.E. _____
 EXP. DATE _____

PLANS PREPARED BY:
 NAME MIKE MATHERNE
 PHONE 208-405-6918
 DATE 2-19-16


JOB NUMBER 9660307
 SCALE: NONE
 PAGE: 1 of 6



LOCATION MAP



WORKZONE 1
 AERIAL # 1



LEGEND

⊕	TYPE 85 ORANGE FLUORESCENT
⊕	TYPE 8 BRIDGE NO. SIGN
⊕	ADDITIONAL WORK ZONE SIGN (INDICATING AHEAD FOR NO/RIGHT TURN OR OBSTRUCTION) USE ONLY
⊕	CHANGING LANE SIGN (USE ONLY)
⊕	WORK AHEAD SIGN
⊕	ROADWORK AHEAD SIGN
⊕	ROADWORK AHEAD SIGN WITH DATE (PLANNED)
⊕	PLANNED
⊕	NO AHEAD STOPPING AHEAD (CONV. ROAD)
⊕	NO AHEAD STOPPING AHEAD
⊕	WORK ZONE LIMIT
⊕	DIRECTION OF TRAFFIC




WASHINGTON UNIVERSITY ACCESS AT ALL TIMES
AERIAL # 1
TYPE OF CONSTRUCTION AERIAL
JOB NUMBER 9660307
PAGE: 2 of 6 SCALE: NONE




ISSUE	DATE
1	2-19-16

LOCATION MAP




WORKZONE 2
AERIAL # 2




LEGEND

- TYPE & BRIDGE WIDTH
- TYPE & BRIDGE ROAD SIGN
- 25' LANE TAPER COVER WITH TRAFFIC SIGNALS
- FOR IMPROVED USE OF BRIDGEWAY & FOR THE BEST TRAFFIC CONTROL CLIP ON SIGN
- PROPOSED SIGN AND POST
- PROPOSED INTERSECTION
- FLASHING AMBER SIGN
- HIGH LEVEL WARNING SIGN WITH SIGN (PLANTED)
- FLAGGER
- 200' TAPER TO STOP SIGN (SEE SIGN)
- 200' TAPER TO STOP SIGN
- WORK ZONE LANES
- DIRECTION OF TRAVEL



MANSFORD UNIVERSITY ADDRESS AT ALL TIMES	
AERIAL # 2	
TYPE OF CONSTRUCTION AERIAL	
JOB NUMBER	9660307
PAGE: 3 OF 6	SCALE: NONE

LOCATION MAP



at&t
 ISSUE 1 DATE 2-19-16


WORKZONE 3
 AERIAL # 3 PHASE 1 OF 2

LEGEND

- TYPE II BARRIERS R/W/S
- TYPE II BARRIERS W/O SIGN
- 20' (11m) WIDENING CROWN (W/C) (11m) BARRIERS BARRIER FOR CONSTRUCTION USE OR DEMARKATION IF NOT USE ONLY
- TRAVEL BARRIERS SIGN CLIP ON SIGN
- PROTECTED SIGN AND POST
- WORKZONES BARRIERS
- PLANNED WORKZONES
- ROAD LEVEL BARRIERS EDGE WITH SIGN PLACEMENT
- FLASERS
- TANS FOR ROAD HO STOPPING AND TO OTHER SIGNALS
- TANSAT FOR ROAD HO STOPPING AND TIE
- WORK ZONE LIGHTS
- BARRIERS OF TRAFFIC



MAINTAIN EGRESS ACCESS AT ALL TIMES
 AERIAL # 3 PHASE 1 OF 2
 TYPE OF CONSTRUCTION
 AERIAL
 JOB NUMBER 9660307
 PAGE 4 of 6 SCALE: NONE






ISSUE	DATE
1	2-19-16


WORKZONE 3
AERIAL # 3 PHASE 2 OF 2

E. RIVER RD
55 MPH



E. RIVER RD
55 MPH

LOCATION MAP



LEGEND	
IT	TYPE II SURFACE SIGN
•	TYPE II SURFACE W/O SIGN
→	DRY SHOULDER
←	DIRT SHOULDER
⊕	PROPOSED SIGN AND POST
⊙	REWORKED INTERSECTION
□	FLARE/BEYOND SIGN
⊕	NEW LEGAL SHOULDER MARK WITH SIGN (PLATE)
+	PLACER
TANS	FOR AUNT TO EXPIRE ... TO ... (DASH HOURS)
TANSAT	FOR AUNT TO EXPIRE ANY TIME
▨	WORK ZONE LIMIT
→	DIRECTION OF TRAFFIC




MAINTENANCE EMPLOYEE ACCESS AT ALL TIMES

AERIAL #3 PHASE 2 OF 2

TYPE OF CONSTRUCTION
AERIAL


JOB NUMBER 9660307

PAGE 6 OF 6 SCALE: NONE



NOTES:

1. New pavement shall be 1" thicker than existing pavement, minimum of 0.25 Ft. New base shall be 1" thicker than existing base, min of 0.50 Ft.
2. Select native material or imported granular material as approved by the Director of Public Works. Backfill with materials equal to or better than the existing pavement and base in quality.
3. Relative compaction of materials shall be tested in accordance with the State of California, Dept. of Transportation Testing Manuals, test method No. California 216 or 231.
4. All existing pavement shall be neatly cut to line prior to trench excavation.
5. Jetting or ponding will be permitted within the street right-of-way with a 3 year bond, when approved by the Director of Public Works.
6. When shown by soil composition and compactability, ninety percent (90%) compaction may be used, when approved by the Director of Public Works.
7. Special bedding and backfill requirements may be shown on the plans or specified in the special provisions.



TYPICAL TRENCH BACKFILL

COUNTY OF SAN JOAQUIN
DEPARTMENT OF PUBLIC WORKS

Approved by:

No.	Revision	Description	Date

Date: DEC 2014

Std. Dwg. No.

R-29

GENERAL PROVISIONS

GOVERNING INSTALLATION OF SUBSURFACE STRUCTURES AND PIPELINES WITHIN COUNTY ROAD RIGHTS-OF-WAY

PUBLIC CONVENIENCE AND SAFETY:

- A. Before obstructing any private driveway entrance or County road traveled way with a trench, spoil bank, equipment or other barrier permitted for any prolonged period of time, the Permittee shall notify the known users of the respective thoroughfare(s) involved, and shall provide access for vehicular and pedestrian traffic to and from the road.
1. Unless otherwise permitted, all work shall be conducted in such a manner that no less than one lane of the existing County road traveled way will be maintained open to public traffic during working hours in a smooth and safe riding condition(s). Two lanes shall be open after working hours.
 2. In cases where road closure is permitted, the permission to close the road will be granted under the condition that the Permittee notify the following persons and/or agencies of the time, the period of closure, and the detour route at least twenty-four (24) hours prior to said road closure.
 - a. The County of San Joaquin Public Works Department
 - b. The County of San Joaquin Sheriff's Office
 - c. The local postal service
 - d. The local fire district
 - e. The local school district
 - f. The local residents involved
- B. Should hazardous conditions relative to the installation operations warrant flagmen, as many capable flagmen as may be necessary shall be provided by the Permittee and stationed in advance of work to warn and direct traffic.
- C. Lights, signs and barricades shall be furnished, erected and maintained by the Permittee for the adequate warning and convenience of the public, with particular attention to be taken in this regard after dark.
- D. Any excess dirt and/or debris which might be a hazard to either automobile or pedestrian traffic, uncontrollable by lights, signs and barricades, shall be removed from the jobsite daily.

STRUCTURES:

- A. Walls of structures shall be such quality and strength that they will resist all pressures and will not crack or be deformed in such a way as to create a hazard or maintenance problem at any time. Therefore, the minimum structural requirements for concrete pipe placed under county road rights-of-way shall conform to the following American Association of State Highway and Transportation Officials (AASHTO) designations.
1. For concrete pipe up to and including thirty-three inches (33") inside diameter, extra strength concrete conforming to AASHTO Designation M 170M.
 2. For concrete pipe thirty-six inches (36") inside diameter and larger, reinforced concrete pipe conforming to AASHTO Designation M 170M Class III.
 3. Plastic pipe conforming to AASHTO Designation M294.
- B. All concrete pipe joints with County road rights-of-way shall be sealed against leakage and/or infiltration with rubber gasket in conformance with Section 65-1:06 of the California Standard Specifications, or with other methods as may be permitted under the Special Provisions.
- C. Cast-in-place concrete pipe, vitrified clay pipe, spiral welded steel pipe, or corrugated aluminum alloy pipe shall not be installed within the County road rights-of-way unless specifically so stated in the Special Provisions, and only under the conditions as provided.
- D. All structures to be buried within the County rights-of-way shall be set at such elevations as to allow minimum coverage of thirty inches (30") to the centerline of the roadways and twelve inches (12") at the bottoms of borrow ditches each side of the roadways. The depths of structures shall be established below a flat plane extending across the rights-of-way, no part of which shall extend above the elevations stated above; manholes, lampholes, valves, etc. not included. Future surface elevations shall be anticipated as nearly as possible and structure elevations shall be established for future adjustments accordingly.
- E. The County hereby reserves the right to specify in the Special Provisions the gage and surface treatment of any galvanized corrugated metal pipe that is to be installed.
- F. All longitudinal utility facilities are to be established (and dimensioned on sketches) from surveyed centerline of road right-of-way, not from right-of-way (border) lines.

REPAIRS OF THE COUNTY RIGHT-OF-WAY:

- A. All excavations shall be backfilled and compacted immediately after work therein has been completed.
- B. Trenched shall not be left open farther than 300 feet in advance of pipe laying operations, or 200 feet to the rear thereof, unless otherwise permitted by the Engineer.
- C. Unless otherwise permitted under the Special Provisions, backfill shall be placed and mechanically compacted in such a manner that the relative compaction throughout the entire fill within the County road right-of-way shall conform to the percentages of compaction as shown on the Trench detail.
- D. Backfill material shall be placed in horizontal uniform layers not to exceed in thickness, before compaction, 0.67 foot in the bedding region, one-foot where 90% compaction is required, and two-feet where 80% compaction is required.
- E. No portion of the excavation(s) shall be compacted by ponding or jetting unless a maintenance bond is provided.
- F. Gravel backfill material shall be utilized only where specifically so stated on the face of the permit. It shall be compacted by means of a high-frequency internal vibrator, the compactor to be a size and type approved by the Engineer. Points of compaction shall not be greater than 18" centers and to the full depth of the lift.
- G. All pavements, curbs, gutters, sidewalks, borrow ditches, pipes, head walls, road signs, trees, shrubbery, and/or other permanent road facilities impaired by or as a result of construction operations at the construction site(s) occupied by materials and/or equipment, shall be restored immediately upon backfilling of the excavation to the original grades and cross sections, and to a condition as good as, or better than existing prior to construction.
- H. All surfacing materials of roadways and driveway approaches cut or damaged by or as a result of construction operations, shall be replaced within ONE WEEK following the backfilling of excavation, weather permitting, with compacted layers of surfacing materials at least as thick as the existing, and no less than two inches (2") of asphalt concrete over six inches (6") of aggregate base, both as specified below.
1. Asphalt Concrete: Combined mineral aggregate shall conform to the quality and gradation requirements for Type "B" one-half inch (1/2) maximum aggregate, coarse or medium gradation as specified in Section 39 of the California Standard Specifications. The bituminous binder to be mixed with mineral aggregate shall be paving asphalt having (Grade PG 64-10), unless otherwise directed by the Engineer. Placement of asphalt concrete surfacing shall conform to the applicable provisions of Section 39 of the California Standard Specifications.
 2. Aggregate Base: Combined mineral aggregates shall conform to the quality and the grading for three-quarter inch (3/4") maximum size aggregate Class 2 Aggregate Base specified in Section 26 of the California Standard Specifications.
- I. Before acceptance of repairs to the County road rights-of-way, all unsightly and detrimental dirt, dust and/or debris shall be removed and the construction areas left in a neat and presentable condition(s).
1. If necessary, County road traveled way and driveway pavements shall be washed with water to remove dirt and dust.
 2. Driveway approaches and field entrance pavements damaged by equipment or spoil banks shall be repaired as directed by the Engineer.
- J. Upon request by the County, any settlement, sagging of surface, or cracking of pavement shall be repaired immediately by and at the sole expense of the Permittee for a period of one year following acceptance of the work.

SPECIAL PROVISIONS

Winter Weather Utility Work

1. **SUPERVISION:** The utility company (permittee) shall furnish full-time supervision of all work to insure compliance with the permit provision.
2. **START OF WORK:** No work within the County right-of-way shall be started until the utility company representative has made an evaluation of weather conditions and has determined the work can be accomplished under the provisions of the permit.
3. **CLEAN PAVEMENT:** Dirt and mud shall not be deposited on the pavement outside the area of work, and if inadvertently tracked onto the road travel way shall be removed immediately.
4. **DAILY RESTORATION:** Private driveways and road intersections shall be restored daily.
5. **WEATHER-TIGHT CONDITIONS:** All trenches shall be filled and compacted, ditches and other drainage facilities regarded and opened, and the entire work area restored to weather-tight condition prior to any rain.