



COUNTY OF SAN JOAQUIN

DEPARTMENT OF PUBLIC WORKS
P.O. BOX 1810-1810 E. HAZELTON AVENUE
STOCKTON, CALIFORNIA 95201
(209) 468-3000
FAX # (209) 468-9324

Permit No: PS-1703701
Date Issued: 11/29/2017
Start Date: 11/29/2017
Exp. Date: 02/01/2018
Project No: PWP730052
Quad: ES

UE/CR/PM NO:31365021

ENCROACHMENT PERMIT

To: PACIFIC GAS & ELECTRIC - STOCKTON
PO BOX 930
STOCKTON, CA 95201

Encroachment Type:

Traffic Control	Devices		
-----------------	---------	--	--

Location:

E/S S WAGNER AV 465' S/O E MAIN ST

In compliance with your request of **11/29/2017**, permission is hereby granted to do work in County right-of-way as shown on attached application and subject to all the terms, conditions and restrictions written below or printed as general or special provisions on any part of this form. See reverse side and attached sheet, if any.

Trench excavations for service connections will not be permitted within ten feet (10') of pavement centerline unless otherwise approved by the Director. Surface of trench patches shall match in kind and be smooth and even with that of abutting surface. Special attention shall be given to depth of utilities through roadside area in anticipation of future drainage facilities, road profile and/or frontage development. All underground utility facilities are to be established and accurately dimensioned on sketches from surveyed centerline of road right of way, or from right of way (border) lines.

Permittee shall call the Department of Public Works, Field Engineering Division (Permit Inspections) at (209)953-7421 at least forty-eight hours prior to beginning any work within the County right of way. All work performed under this permit shall conform to the rules and regulations pertaining to safety established by the California Division of Industrial Safety and Cal-OSHA.

The jobsite shall be kept in a safe condition at all times by the daily removal of any excess dirt or debris which might be a hazard to either pedestrian or automobile traffic. All necessary traffic convenience and warning devices and personnel shall be provided, placed and maintained by and at the sole expense of the Permittee in accordance with the latest edition of the CALTRANS Manual of Traffic Control.

After completion of the work permitted herein, all debris, lumber, barricades, or any excess material shall be removed and the jobsite left in a neat workmanlike manner. Immediately following completion of construction permitted herein, Permittee shall fill out and mail notice of completion (see attached post card) provided by Grantor.

Special Comments:

Traffic Control Per MUTCD****Work shall not be permitted within the San Joaquin County right-of-way between November 1 and March 31 without prior authorization from the San Joaquin County Field Engineering Division, contact them at (209) 953-7421****


FORMS:

SS/WW		
-------	--	--

Est. Permit Fee: \$436.00

KRIS BALAJI, Director
Department of Public Works

WHITE -Permittee
GOLDENROD -PWD Central File
YELLOW -Field Inspection
PINK -Permit Section

By: 
Permit Section

ENCROACHMENT PERMIT GENERAL PROVISIONS

13-1

1. This permit is issued under and subject to all laws and ordinances of agencies-governing the encroachment herein permitted. See the following references:

STREETS AND HIGHWAYS CODE

1. Division 1, Chapter 3
2. Division 2, Chapter 2, Section 942
3. Division 2, Chapter 4, Section 1126
4. Division 2, Chapter 5.5 and Chapter 6

SAN JOAQUIN COUNTY ORDINANCES NUMBERED: 324, 441, 648, 662, 672, 695, 700, 860, 892, 3359, and 3675.

2. It is understood and agreed by the Permittee that the performance of any work under this permit shall constitute an acceptance of all the provisions contained herein and failure on the Permittee's part to comply with any provision will be cause for revocation of this permit. Except as otherwise provided for public agencies and franchise holders, this permit is revocable on five days notice.
3. All work shall be done subject to the supervision of and the satisfaction of the grantor. The Permittee shall at all times during the progress of the work keep the County Highway in as neat and clean condition as is possible and upon completion of the work authorized herein, shall leave the County Highway in a thoroughly neat, clean and usable condition.
4. The Permittee also agrees by the acceptance of this permit to properly maintain any encroachment structure placed by the Permittee on any part of the County Highway and to immediately repair any damage to any portion of the highway, which occurs as a result of the maintenance of the said encroachment structure, until such time as the Permittee may be relieved of the responsibility for such maintenance by the County of San Joaquin.
5. The Permittee also agrees by the acceptance of this permit to make, at its own expense, such repairs as may be deemed necessary by the County Department of Public Works.
6. It is further agreed by the Permittee that whenever construction, reconstruction or maintenance work upon the highway is necessary, the installation provided for herein shall, upon request of the County Department of Public Works, be immediately moved or removed by and at the sole expense of the Permittee.
7. No material used for fill or backfill in the construction of the encroachment shall be borrowed or taken from within the County right of way.
8. All work shall be planned and carried out with as little inconvenience as possible to the traveling public. No material shall be stacked within eight feet (8') of the edge of the pavement or traveled way unless otherwise provided herein. Adequate provision shall be made for the protection of the traveling public. Traffic control standards shall be utilized including barricades; approved signs and lights; and flagmen, as required by the particular work in progress.
9. The Permittee, by the acceptance of this permit, shall assume full responsibility for all liability for personal injury or damage to property which may arise out of the work herein permitted or which may arise out of the failure of the part of the Permittee to properly perform the work provided under this permit. In the event any claim of such liability is made against the County of San Joaquin or any department, official or employee thereof, the Permittee shall defend, indemnify, and hold each of them harmless for such claim.
10. All backfill material is to be moistened as necessary and thoroughly compacted with mechanical means. If required by the County Director of Public Works, such backfill shall consist of gravel or crushed rock. The Permittee shall maintain the surface over structures placed hereunder as may be necessary to insure the return of the roadway to a completely stable condition and until relieved of such responsibility by the County Department of Public Works. Wherever a gravel, crushed rock or asphalt surface is removed or damaged in the course of work related to the permitted encroachment, such material shall either be separately stored and replaced in the roadway as nearly as possible in its original state or shall be replaced in kind, and the roadway shall be left in at least as good a condition as it was before the commencement of operations of placing the encroachment structure.
11. Whenever it becomes necessary to secure permission from abutting property owners for the proposed work, such authority must be secured by the Permittee prior to starting work.
12. The current and future safety and convenience of the traveling public shall be given every consideration in the location and methods of construction utilized.
13. The Permittee is responsible for the preservation of survey monuments located within the area of work herein permitted. Prior to the start of construction, survey monuments that potentially may be disturbed shall be located and referenced by a Licensed Land Surveyor, and a Corner Record filed with the County Surveyor. Any Survey Monuments disturbed during the course of construction shall be reestablished by a Licensed Land Surveyor and another Corner Record filed with the County Surveyor. (Land Surveyors' Act Section 8771)
14. Prior to any excavation, the Permittee shall notify USA North (Underground Service Alert of Northern California and Nevada) at 811 or 800-227-2600 forty-eight (48) hours in advance.

APPLICATION FOR ENCROACHMENT PERMIT

PLEASE PRINT:

Date 11/13/17

To: San Joaquin County
Department of Public Works

PG&E

(Applicant Name)

4040 West Lane

(Mailing Address)

Stockton, CA. 95204

(City, State, Zip Code)

(209) 409-2083

(Area Code - Telephone Number)

WAT8@PGE.COM

(Email Address)

OFFICE USE ONLY

JOB #	<u>730052</u>	REF #	
APN		CR #	
EXP. DATE	<u>2-1-17</u>		
VALID	<u>11-29-17</u> TO <u>2-1-17</u>	DRIVEWAYS:	
STREET	<u>Wagner</u>	*	
AREA	<u>Stockton</u> QUAD <u>ES</u>	*	
TYPE	<u>Bellhole</u>	*	
FORMS	<u>SSWW R29</u>		
NOTES			

Sketch (Detailed plans may be submitted)

SEE ATTACHED DRAWING


PM # **31365021**

The undersigned hereby applies for permission to excavate, construct and/or otherwise encroach on County Highway Right-of-Way on the E side of S. Wagner Ave approximately 465 feet/mile S of E Main St., Stockton, by performing the following work (description of work):

Cut off service at main.

Work will commence on or after 12/11/17 for approximately 60 days.

I, the undersigned, certify that I am the owner of the respective property, or am qualified to represent the owner and agree to do the work described above in accordance with the rules and regulations of San Joaquin County and subject to inspection and approval.


Signature of Applicant - Title

11/13/17
Date

SPECIAL CONDITIONS FOR
ENCROACHMENT PERMIT

1. Maintain traffic controls for all roads. Traffic control delays shall not exceed 15 minutes. Two-way traffic shall be maintained during non-working hours with excavated areas backfilled or plated. During working hours, two-way traffic control shall be maintained with one lane open and appropriate flaggers. The contractor shall submit traffic control plans for all signing, detours, and any lane closure impacting County right-of-way.
2. Access to all properties shall be maintained at all times except when work is occurring at the access point. Minimal delays will be allowed to provide access within the work zone area. Driveway access shall be fully restored at the end of each workday. Driveways disturbed by the contractor shall be replaced with in-kind or better materials.
3. Residents and businesses shall be notified in writing, as approved by the County, 48 hours in advance of any impacts to their access.
4. Any areas where parking is to be restricted shall have signs noting the restrictions in place at least 48 hours in advance.
5. Existing fences shall not be removed without written consent of the property owner. Such consent shall be submitted to the County prior to the removal. Fences removed shall be restored with in-kind or better materials. Restored fences shall not encroach into County right-of-way.
6. Work shall not be permitted within the San Joaquin County right-of-way between November 1 and March 31 without prior authorization from the San Joaquin County Department of Public Works Field Engineering Division, contact them at 209-953-7421.
7. All destroyed or obliterated pavement markings must be replaced in kind by the permittee. Typical pavement markings include but not limited to lane lines, centerlines, stop and stop ahead legends, limit lines, raised pavement markers and miscellaneous delineators.
8. The Permittee is responsible for the preservation of survey monuments located within the area of work herein permitted. Prior to the start of construction, survey monuments that potentially may be disturbed shall be located and referenced by a Licensed Land Surveyor, and a Corner Record filed with the County Surveyor. Any Survey Monuments disturbed during the course of construction shall be reestablished by a Licensed Land Surveyor and another Corner Record filed with the County Surveyor. (Land Surveyors' Act Section 8771)
9. All pipe and pipeline related facilities including, but not limited to, valves, utility boxes and vaults, and frames and covers shall be maintained by PACIFIC GAS & ELECTRIC, including any facilities that are abandoned in place. PACIFIC GAS & ELECTRIC shall be responsible for any and all costs associated with the removal, relocation and/or adjustment of these facilities as determined by the County at PACIFIC GAS & ELECTRIC's expense. (Streets and Highways Code Section 1463)
10. All future maintenance of the pipeline and related facilities within the County right-of-way will require a San Joaquin County Encroachment Permit.

11. Trenches shall be maintained in a smooth and even condition to the satisfaction of the County throughout the project limits at all times.
12. All trenches shall be completely backfilled or shored and plated at the end of each workday, and the roadway restored to two-way traffic. If plating is to be used, a trench shoring and plating plan suitable for traffic loadings shall be prepared by a registered civil engineer and submitted for prior approval by the County.
13. The contractor shall use San Joaquin County Improvement Standard R-29 when backfilling trenches within the County right-of-way. Where the existing road structural section is below standard, a minimum section of 3 inches of asphalt concrete over 8 inches of aggregate base shall be required.
14. Final paving for trench repair or road resurfacing shall be per Caltrans' specifications and shall not occur between November 1 and March 31, without prior authorization from the San Joaquin County Department of Public Works Field Engineering Division, contact them at 209-953-7421.
15. No paving joints are allowed within paved shoulder; contractor shall pave all the way to outer edge of paved shoulder.
16. Class II Aggregate Base shoulder backing is required from the edge of pavement, a minimum of 4-inches thick by 4-feet wide.
17. Contractor shall establish existing roadway and drainage grades within the construction area. Any repair to roadways and adjacent areas shall match existing grades. Any proposed grade changes shall receive prior approval from County.
18. Above ground vaults, panels and/or other similar facilities will be allowed within the right-of-way if located as far to the outside edge as possible. Utility vaults shall be located a minimum of 4'-0" from edge of pavement.
19. County roads shall be kept clean from mud and debris at all times along the access points and work zone areas during entire project. All standard roadway striping and signage shall be clearly visible, maintained and restored throughout the construction zone during and after the project.
20. In addition to standard dust control measures, streets shall be maintained in a clean condition, free of dirt, mud and debris during construction activities. The contractor shall provide daily, or as needed, street sweeping using a modern mechanical or vacuum-assisted street sweeper.
21. The contractor shall not conduct construction operations in rain or heavy fog conditions.

	Pacific Gas & Electric Company Gas Service Record TD-9500P-14-F01		GAS SERVICE RECORD		<input type="checkbox"/> Special Facilities <input type="checkbox"/> (CP 10%) <input type="checkbox"/> Existing (10%) Class Location: <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4 No. of Floors: _____	
	Map No. <u>3005</u> Notif. No. <u>113792242</u> PM Order No. <u>31365021</u> Leak No. _____ S.O. No. <u>17479</u>		Plot No. <u>D8</u> Block <u>35</u> City <u>STOCKTON</u> Address <u>952 S. WAGNER RD</u>		Agreement: <input type="checkbox"/> Verbal <input type="checkbox"/> Written Applicant/Tract Name <u>RMCI BUILDERS</u> Lot No. _____ EST LAN ID <u>M353</u> Date Issued <u>11/10/17</u>	
<input type="checkbox"/> PROPOSED <input checked="" type="checkbox"/> EXISTING FACILITY: MAOP <u>55</u> PSIG <u>W/C</u>			Main Trench Occupants: <input checked="" type="checkbox"/> None <input type="checkbox"/> Electric <input type="checkbox"/> Telephone <input type="checkbox"/> CATV <input type="checkbox"/> Other		Posted By Mapping: _____ LAN ID _____ Signature _____ Date ____/____/____	
OFF: <input checked="" type="checkbox"/> Main <input type="checkbox"/> 2" HP <input type="checkbox"/> PE <input type="checkbox"/> STL <input type="checkbox"/> Aldyl-A <input type="checkbox"/> Service Size & Pressure <input type="checkbox"/> CI <input type="checkbox"/> CU			Inserted <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes Casing size & material: _____ Casing: <input type="checkbox"/> Double Casing size & material: _____		On <u>EAST</u> Side <u>S. WAGNER RD.</u> In _____ Out <u>12'</u>	
<input type="checkbox"/> PROPOSED <input checked="" type="checkbox"/> EXISTING SERVICE LOCATION: Service: On <u>EAST</u> Side <u>S. WAGNER RD., 465' N/O E. MAIN ST.</u>			Insert: <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes <input type="checkbox"/> Double Casing size & material: _____ Casing size & material: _____		JOB TYPE <input type="checkbox"/> NEW SERVICE <input type="checkbox"/> STUB SERVICE * <input type="checkbox"/> STUB COMPLETION ** <input type="checkbox"/> BRANCH SERVICE REF. NO. _____ <input type="checkbox"/> CURB METER <input type="checkbox"/> METER CHANGE <input type="checkbox"/> MANIFOLD <input type="checkbox"/> CONVERT TO MAIN <input type="checkbox"/> UPRATE <input type="checkbox"/> REPLACEMENT <input type="checkbox"/> PARTIAL <input type="checkbox"/> COMPLETE <input type="checkbox"/> TRANSFER <input type="checkbox"/> ALTER / INSPECTION <input checked="" type="checkbox"/> CUT-OFF <input checked="" type="checkbox"/> AT MAIN <input type="checkbox"/> AT P/L <input type="checkbox"/> AT BRANCH <input type="checkbox"/> OTHER	
Size: <u>3/4"</u> <input type="checkbox"/> PE2406 <input type="checkbox"/> PE3408 <input type="checkbox"/> Aldyl-A <input checked="" type="checkbox"/> STL <input type="checkbox"/> CU			SVC Trench Occupied With: <input checked="" type="checkbox"/> None <input type="checkbox"/> Electric <input type="checkbox"/> Phone <input type="checkbox"/> CATV <input type="checkbox"/> Other _____		Total Load _____ SCFH Delivery Pressure _____ TBA Elevation _____	
Riser: Size <u>3/4"</u> <input type="checkbox"/> Inside <input checked="" type="checkbox"/> Outside <input type="checkbox"/> W/Bypass Pre-Fab Non-Corrudible: <input type="checkbox"/> Regular <input type="checkbox"/> Short <input type="checkbox"/> Long Curb Valve: <input type="checkbox"/> Metal <input type="checkbox"/> PL <input checked="" type="checkbox"/> None <input type="checkbox"/> Steel Encased-Plastic Insert <input checked="" type="checkbox"/> Steel Riser <input type="checkbox"/> CU Riser			No. of Outlets <u>1</u> Res. Meter(s) Qty./Size _____ Reg. Size/Type: _____ Orifice: _____ Comm. Meter(s) Qty./Size _____ Monitor Size/Type: _____ Orifice: _____ C/O Data <u>52'</u> Ft. of <u>3/4"</u> In. Yr. Install <u>1943</u> Type: <input checked="" type="checkbox"/> STL <input type="checkbox"/> PL <input type="checkbox"/> CU Reason: <input type="checkbox"/> Leakage <input checked="" type="checkbox"/> Other Transfer From _____ Main On _____ Side _____ In _____ Out _____ Instructions & Cautions: <u>CUT OFF SERVICE AT MAIN.</u>			
EXCAVATED BY: PG&E APPLICANT _____ FRANCHISE / STUB <input checked="" type="checkbox"/> PRIVATE / COMPLETION <input checked="" type="checkbox"/>		INSTALLED BY: PG&E APPLICANT _____ FRANCHISE / STUB <input type="checkbox"/> PRIVATE / COMPLETION <input type="checkbox"/>		BORE: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO Remarks _____		
*DATE STUB INSTALLED ____/____/____ Foreman LAN ID _____ Signature _____ <input type="checkbox"/> Electronic Marker installed MANUFACTURER _____ DATE MANUFACTURED ____/____/____ **DATE COMPLETED ____/____/____ Foreman LAN ID _____ Signature _____ MANUFACTURER _____ DATE MANUFACTURED ____/____/____			WORK DONE: (Show corrections to service and main data above) _____ Ft. Main to P/L _____ Ft. P/L to End of Stub _____ Ft. End of Stub to Riser Total Ft. _____			
TEST DATA: (Per No. Doc. A-34) <input type="checkbox"/> Soap Test STUB _____ PSIG for _____ Minutes Foreman LAN ID _____ Signature _____ Date ____/____/____ COMPLETION _____ PSIG for _____ Minutes Foreman LAN ID _____ Signature _____ Date ____/____/____ For services operating with an MAOP above 60 PSIG, attach a copy of the Strength Test Pressure Report.			WELDING INSPECTION PER PG&E No. Doc. D-40 Signature _____ LAN ID _____ Date _____ RISER VALVE MFG: _____			
CATHODIC PROTECTION: CPA No. <u>300503</u> Main under protection <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO <input type="checkbox"/> RISER Install cathodic protection (Per No. Doc. D-16) <input type="checkbox"/> VALVE <input type="checkbox"/> SVC <input type="checkbox"/> Existing <input type="checkbox"/> New: No. Installed _____ <input type="checkbox"/> MAIN Size: _____ Lb. Anode Type: <input type="checkbox"/> MAG <input type="checkbox"/> ZINC			GALVANIC CP SYSTEMS: Reading _____ Date ____/____/____ Reading _____ Date ____/____/____ Reading _____ Date ____/____/____ Qualified Employee Signature & LAN ID _____			
LOCATING WIRE CONNECTIONS: SVC Wire Size _____ TERM. AT: <input type="checkbox"/> MAIN <input type="checkbox"/> BRANCH TERM. AT: <input type="checkbox"/> RISER <input type="checkbox"/> SVC <input type="checkbox"/> Bonded <input type="checkbox"/> Bonded <input type="checkbox"/> Wrapped around Tee <input type="checkbox"/> Strapped to Riser <input type="checkbox"/> N/A <input type="checkbox"/> N/A <input type="checkbox"/> Terminated at _____						

Pre 1972 Pipe Wrap Asbestos Stamp
(TD-471P-01)

1. Estimating to Complete:
 Year Pipe Installed: _____
 Historical Results, Contains Asbestos? ☐ Yes ☐ No ☐ Unknown

Pre 1972 AND Unknown - Sample is Required

2. Field (Sampler) to Complete: LAN ID _____
 Date Sampled: _____ Sample ID: _____


3. Mapping to Complete: LAN ID _____
 Asbestos Result: ☐ Yes _____% OR ☐ No (ND)

GAS SERVICE DEACTIVATION	
REQUESTED BY: _____	
REQUIRED COMPLETION DATE: _____	
<input type="checkbox"/> SERVICE C/O @ MAIN / BRANCH <input type="checkbox"/> SERVICE C/O @ P/L <input type="checkbox"/> SITE EXCAVATED - NOT DEACTIVATED - NOT LOCATABLE <input type="checkbox"/> NOT EXCAVATED - NOT DEACTIVATED - NOT LOCATABLE	
COMMENTS: _____	
FORWARD'S SIGNATURE: _____	
FORWARD'S LAN ID: _____	DATE COMPLETED: _____

UTILITY TYPICAL APPLICATIONS

UTA-4 Lane Closure on Street, Self-regulating

1. The traffic control procedure shown is **appropriate only for low-volume, low-speed streets / roads.**
2. Traffic can regulate itself when volumes are low and the length of the work space is short, if drivers can readily see the roadway beyond.
3. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.
4. The one-lane, two-way taper is used in advance of an activity area that occupies part of a two-way roadway in such a manner that a portion of the roadway is used alternately by traffic on both directions. Typically, a flagger controls traffic. A short taper of 100 feet maximum with channelizing devices (cones, etc.) at approximately 16 foot spacing should be used to guide traffic into the one-way section.



SEE:

- TABLE 1 for Buffer Length (page 28)
- TABLE 4 for "L" & Channelizer (cones, etc.) Quantity (page 28)

NOTE: LOCAL REGULATIONS MAY VARY.

SIGN SPACING	DISTANCE
ROAD TYPE	A
Urban - 25 MPH or less	200'
Urban - 30 MPH or more	350'
Rural	500'
Expressway/Freeway	1000'

PM 31365021

11/13/2017

PGFPM1A

© Copyright 2002 InCom, Inc. All rights reserved.

GENERAL PROVISIONS

GOVERNING INSTALLATION OF SUBSURFACE STRUCTURES AND PIPELINES WITHIN COUNTY ROAD RIGHTS-OF-WAY

PUBLIC CONVENIENCE AND SAFETY:

- A. Before obstructing any private driveway entrance or County road traveled way with a trench, spoil bank, equipment or other barrier permitted for any prolonged period of time, the Permittee shall notify the known users of the respective thoroughfare(s) involved, and shall provide access for vehicular and pedestrian traffic to and from the road.
 1. Unless otherwise permitted, all work shall be conducted in such a manner that no less than one lane of the existing County road traveled way will be maintained open to public traffic during working hours in a smooth and safe riding condition(s). Two lanes shall be open after working hours.
 2. In cases where road closure is permitted, the permission to close the road will be granted under the condition that the Permittee notify the following persons and/or agencies of the time, the period of closure, and the detour route at least twenty-four (24) hours prior to said road closure.

a. The County of San Joaquin Public Works Department	d. The local fire district
b. The County of San Joaquin Sheriff's Office	e. The local school district
c. The local postal service	f. The local residents involved
- B. Should hazardous conditions relative to the installation operations warrant flagmen, as many capable flagmen as may be necessary shall be provided by the Permittee and stationed in advance of work to warn and direct traffic.
- C. Lights, signs and barricades shall be furnished, erected and maintained by the Permittee for the adequate warning and convenience of the public, with particular attention to be taken in this regard after dark.
- D. Any excess dirt and/or debris which might be a hazard to either automobile or pedestrian traffic, uncontrollable by lights, signs and barricades, shall be removed from the jobsite daily.

STRUCTURES:

- A. Walls of structures shall be such quality and strength that they will resist all pressures and will not crack or be deformed in such a way as to create a hazard or maintenance problem at any time. Therefore, the minimum structural requirements for concrete pipe placed under county road rights-of-way shall conform to the following American Association of State Highway and Transportation Officials (AASHTO) designations.
 1. For concrete pipe up to and including thirty-three inches (33") inside diameter, extra strength concrete conforming to AASHTO Designation M 170M
 2. For concrete pipe thirty-six inches (36") inside diameter and larger, reinforced concrete pipe conforming to AASHTO Designation M 170M Class III
 3. Plastic pipe conforming to AASHTO Designation M294.
- B. All concrete pipe joints within County road rights-of-way shall be sealed against leakage and/or infiltration with rubber gasket in conformance with Section 65-1:06 of the California Standard Specifications, or with other methods as may be permitted under the Special Provisions.
- C. Cast-in-place concrete pipe, vitrified clay pipe, spiral welded steel pipe, or corrugated aluminum alloy pipe shall not be installed within the County road rights-of-way unless specifically so stated in the Special Provisions, and only under the conditions as provided.
- D. All structures to be buried within the County rights-of-way shall be set at such elevations as to allow minimum coverage of thirty inches (30") to the centerline of the roadways and twelve inches (12") at the bottoms of borrow ditches each side of the roadways. The depths of structures shall be established below a flat plane extending across the rights-of-way, no part of which shall extend above the elevations stated above; manholes, lampholes, valves, etc. not included. Future surface elevations shall be anticipated as nearly as possible and structure elevations shall be established for future adjustments accordingly.
- E. The County hereby reserves the right to specify in the Special Provisions the gage and surface treatment of any galvanized corrugated metal pipe that is to be installed.
- F. All longitudinal utility facilities are to be established (and dimensioned on sketches) from surveyed centerline of road right-of-way, not from right-of-way (border) lines.

REPAIRS OF THE COUNTY RIGHT-OF-WAY:

- A. All excavations shall be backfilled and compacted immediately after work therein has been completed.
- B. Trenched shall not be left open farther than 300 feet in advance of pipe laying operations, or 200 feet to the rear thereof, unless otherwise permitted by the Engineer.
- C. Unless otherwise permitted under the Special Provisions, backfill shall be placed and mechanically compacted in such a manner that the relative compaction throughout the entire fill within the County road right-of-way shall conform to the percentages of compaction as shown on the Trench detail.
- D. Backfill material shall be placed in horizontal uniform layers not to exceed in thickness, before compaction, 0.67 foot in the bedding region, one-foot where 90% compaction is required, and two-feet where 80% compaction is required.
- E. No portion of the excavation(s) shall be compacted by ponding or jetting unless a maintenance bond is provided.
- F. Gravel backfill material shall be utilized only where specifically so stated on the face of the permit. It shall be compacted by means of a high-frequency internal vibrator, the compactor to be a size and type approved by the Engineer. Points of compaction shall not be greater than 18" centers and to the full depth of the lift.
- G. All pavements, curbs, gutters, sidewalks, borrow ditches, pipes, head walls, road signs, trees, shrubbery, and/or other permanent road facilities impaired by or as a result of construction operations at the construction site(s) occupied by materials and/or equipment, shall be restored immediately upon backfilling of the excavation to the original grades and cross sections, and to a condition as good as, or better than existing prior to construction.
- H. All surfacing materials of roadways and driveway approaches cut or damaged by or as a result of construction operations, shall be replaced within ONE WEEK following the backfilling of excavation, weather permitting, with compacted layers of surfacing materials at least as thick as the existing, and no less than two inches (2") of asphalt concrete over six inches (6") of aggregate base, both as specified below.
 1. Asphalt Concrete: Combined mineral aggregate shall conform to the quality and gradation requirements for Type "B" one-half inch (1/2) maximum aggregate, coarse or medium gradation as specified in Section 39 of the California Standard Specifications. The bituminous binder to be mixed with mineral aggregate shall be paving asphalt having (Grade PG 64-10), unless otherwise directed by the Engineer. Placement of asphalt concrete surfacing shall conform to the applicable provisions of Section 39 of the California Standard Specifications.
 2. Aggregate Base: Combined mineral aggregates shall conform to the quality and the grading for three-quarter inch (3/4") maximum size aggregate Class 2 Aggregate Base specified in Section 26 of the California Standard Specifications.
- I. Before acceptance of repairs to the County road rights-of-way, all unsightly and detrimental dirt, dust and/or debris shall be removed and the construction areas left in a neat and presentable condition(s).
 1. If necessary, County road traveled way and driveway pavements shall be washed with water to remove dirt and dust.
 2. Driveway approaches and field entrance pavements damaged by equipment or spoil banks shall be repaired as directed by the Engineer.
- J. Upon request by the County, any settlement, sagging of surface, or cracking of pavement shall be repaired immediately by and at the sole expense of the Permittee for a period of one year following acceptance of the work.

SPECIAL PROVISIONS

Winter Weather Utility Work

1. SUPERVISION: The utility company (permittee) shall furnish full-time supervision of all work to insure compliance with the permit provision.
2. START OF WORK: No work within the County right-of-way shall be started until the utility company representative has made an evaluation of weather conditions and has determined the work can be accomplished under the provisions of the permit.
3. CLEAN PAVEMENT: Dirt and mud shall not be deposited on the pavement outside the area of work, and if inadvertently tracked onto the road travel way shall be removed immediately.
4. DAILY RESTORATION: Private driveways and road intersections shall be restored daily.
5. WEATHER-TIGHT CONDITIONS: All trenches shall be filled and compacted, ditches and other drainage facilities regarded and opened, and the entire work area restored to weather-tight condition prior to any rain.