

# **COUNTY OF SAN JOAQUIN**

#### DEPARTMENT OF PUBLIC WORKS

P.0. BOX 1810-1810 E. HAZELTON AVENUE STOCKTON, CALIFORNIA 95201 (209) 468-3000 FAX # (209) 468-9324 Permit No: **PS-1900680**Date Issued: 03/13/2019
Start Date: 03/15/2019
Exp. Date: 10/01/2019
Project No: PWP730052

Quad: NW

UE/CR/PM NO:43668833

## **ENCROACHMENT PERMIT**

To: PACIFIC GAS & ELECTRIC - STOCKTON PO BOX 930

STOCKTON, CA 95201

Encroachment Type:		
Driveway Approach	Asphalt Replacement	

#### Location:

N/S OF MORSE RD. 342' E/O HAM LN.

In compliance with your request of <u>03/13/2019</u>, permission is hereby granted to do work in County right-of-way as shown on attached application and subject to all the terms, conditions and restrictions written below or printed as general or special provisions on any part of this form. See reverse side and attached sheet, if any.

Trench excavations for service connections will not be permitted within ten feet (10') of pavement centerline unless otherwise approved by the Director. Surface of trench patches shall match in kind and be smooth and even with that of abutting surface. Special attention shall be given to depth of utilities through roadside area in anticipation of future drainage facilities, road profile and/or frontage development. All underground utility facilities are to be established and accurately dimensioned on sketches from surveyed centerline of road right of way, or from right of way (border) lines.

Permittee shall call the Department of Public Works, Field Engineering Division (Permit Inspections) at (209)953-7421 at least forty-eight hours prior to beginning any work within the County right of way. All work performed under this permit shall conform to the rules and regulations pertaining to safety established by the California Division of Industrial Safety and Cal-OSHA.

The jobsite shall be kept in a safe condition at all times by the daily removal of any excess dirt or debris which might be a hazard to either pedestrian or automobile traffic. All necessary traffic convenience and warning devices and personnel shall be provided, placed and maintained by and at the sole expense of the Permittee in accordance with the latest edition of the CALTRANS Manual of Traffic Control.

After completion of the work permitted herein, all debris, lumber, barricades, or any excess material shall be removed and the jobsite left in a neat workmanlike manner. Immediately following completion of construction permitted herein, Permittee shall fill out and mail notice of completion (see attached post card) provided by Grantor.

Special Con	mments:				If the Bloom Line	
Traffic Con	trol Per MUTCD					
FORMS:	SS/WW, R-17	*	<u> </u>			
			-	<del></del>		

Est. Permit Fee: \$490.00

WHITE -Permittee
GOLDENROD -PWD Central File
YELLOW -Field Inspection
PINK -Permit Section

y: Permit Section

KRIS BALAJI, Director
Department of Public Works

## ENCROACHMENT PERMIT GENERAL PROVISIONS

 This permit is issued under and subject to all laws and ordinances of agencies-governing the encroachment herein permitted. See the following references:

STREETS AND HIGHWAYS CODE

- 1. Division 1, Chapter 3
- 2. Division 2, Chapter 2, Section 942
- 3. Division 2, Chapter 4, Section 1126
- 4. Division 2, Chapter 5.5 and Chapter 6

S'AN JOAQUIN COUNTY ORDINANCES NUMBERED: 324, 441, 648, 662, 672, 695, 700, 860, 892, 3359, and 3675...

- 2. It is understood and agreed by the Permittee that the performance of any work under this permit shall constitute an acceptance of all the provisions contained herein and failure on the Permittee's part to comply with any provision will be cause for revocation of this permit Except as otherwise provided for public agencies and franchise holders, this permit is revocable on five days notice.
- 3. All work shall be done subject to the supervision of and the satisfaction of the grantor. The Permittee shall at all times during the progress of the work keep the County Highway in as neat and clean condition as is possible and upon completion of the work authorized herein, shall leave the County Highway in a thoroughly neat, clean and usable condition.
- 4. The Permittee also agrees by the acceptance of this permit to properly maintain any encroachment structure placed by the Permittee on any part of the County Highway and to immediately repair any damage to any portion of the highway, which occurs as a result of the maintenance of the said encroachment structure, until such time as the Permittee may be relieved of the responsibility for such maintenance by the County of San Joaquin.
- The Permittee also agrees by the acceptance of this permit to make, at its own expense, such repairs as may be deemed necessary by the County Department of Public Works.
- 6. It is further agreed by the Permittee that whenever construction, reconstruction or maintenance work upon the highway is necessary, the installation provided for herein shall, upon request of the County Department of Public Works, be immediately moved or removed by and at the sole expense of the Permittee.
- 7. No material used for fill or backfill in the construction of the encroachment shall be borrowed or taken from within the County right of way.
- 8. All work shall be planned and carried out with as little inconvenience as possible to the traveling public. No material shall be stacked within eight feet (8') of the edge of the pavement or traveled way unless otherwise provided herein. Adequate provision shall be made for the protection of the traveling public. Traffic control standards shall be utilized including barricades; approved signs and lights; and flagmen, as required by the particular work in progress.
- 9. The Permittee, by the acceptance of this permit, shall assume full responsibility for all liability for personal injury or damage to property which may arise out of the work herein permitted or which may arise out of the failure of the part of the Permittee to properly perform the work provided under this permit. In the event any claim of such liability is made against the County of San Joaquin or any department, official or employee thereof, the Permittee shall defend, indexinity, and hold each of them harmless for such claim.
- 10. All backfill material is to be moistened as necessary and thoroughly compacted with mechanical means. If required by the County Director of Public Works, such backfill shall consist of gravel or crushed rock. The Permittee shall maintain the surface over structures placed hereunder as may be necessary to insure the return of the roadway to a completely stable condition and until relieved of such responsibility by the County Department of Public Works. Wherever a gravel, crushed rock or asphalt surface is removed or damaged in the course of work related to the permitted encroachment, such material shall either be separately stored and replaced in the roadway as nearly as possible in its original state or shall be replaced in kind, and the roadway shall be left in at least as good a condition as it was before the commencement of operations of placing the encroachment structure.
- 11. Whenever it becomes necessary to secure permission from abutting property owners for the proposed work, such authority must be secured by the Permittee prior to starting work.
- 12. The current and future safety and convenience of the traveling public shall be given every consideration in the location and methods of construction utilized.
- 13. The Permittee is responsible for the preservation of survey monuments located within the area of work herein permitted. Prior to the start of construction, survey monuments that potentially may be disturbed shall be located and referenced by a Licensed Land Surveyor, and a Corner Record filed with the County Surveyor. Any Survey Monuments disturbed during the course of construction shall be reestablished by a Licensed Land Surveyor and another Corner Record filed with the County Surveyor. (Land Surveyors' Act Section 8771)
- 14. Prior to any excavation, the Permittee shall notify USA North (Underground Service Alert of Northern California and Nevada) at 811 or 800-227-2600 forty-eight (48) hours in advance.

# APPLICATION FOR ENCROACHMENT PERMIT

ΡI	_EA	SE	P	RI	N	<b>T</b> :

Date	2/12/2019		OFFICE U	SE ONLY	
То:	San Joaquin County Department of Public Works	JOB# APN EXP. DATE	130052-6	REF # _ CR #	
	PG&E PM 43668833	VALID	3/15/19 TO	10/1/19	DRIVEWAYS:
	(Applicant Name)	STREET	MORSE RD		*
	4040 West Lane	AREA TYPE	BELL HOLE QUAD	NW	*
	(Mailing Address)	FORMS NOTES	Sofww, de l	-17	
	Stockton, CA 95204	NOIES			
	(City, State, Zip Code)				
	(209) 470 - 2300	·			
	(Area Code - Telephone Number)				
	s6pz@pge.com (Email Address)				
Landa and Andrewson Co.	Crew to call SJ County Inspector at (20 When calling, crew shall request "rain Novemb	9) 953-74 oclearance oer through	" for any work durir	<b>before</b> work ng <b>winter mo</b> r	starts. nths
	Toveray	Rd approximate lowing work (	ely 342' EAST of Ham L description of work):	ane,	
			for any and a state.	100	dava
Work w	ill commence on or after2/15/2019		_ tor approximately	180	days.
I, the u	ndersigned, certify that I am the owner of the respective scribed above in accordance with the rules and regula	e property, or ations of San	am qualified to represel Joaquin County and sub	nt the owner and ject to inspection	agree to do the and approval.
	Sur Petra Parit Fair	litato-	2/12/2019		
	Signature of Applicant - Title	•	Da	ite	





### **Department of Public Works**

Kris Balaji, Director of Public Works

Fritz Buchman, Deputy Director/Development Michael Selling, Deputy Director/Engineering Jim Stone, Deputy Director/Operations Kristi Rhea, Manager of Strategic Initiatives

# **Acknowledgement of Monument Preservation**

I, <u>Brett Brusatori</u> , a duly Licensed Land Surveyor or a Professional Engineer (Please print)	
authorized to perform Land Surveying in the State of California, Registration No. 8775	
hereby acknowledge and accept all responsibility for the monument preservation as required	
per Section 8771(a-f) of the Business and Professions Code within the bounds of the	
construction activity permitted by San Joaquin County Permit No. <u>#8-Paucibo</u> . PM# <u>43668833</u>	_
I further acknowledge that I am hereby responsible for the Acknowledgement of Monument	
Preservation prior to final acceptance of the construction activity.	
CONAL LAWD SI	

Seal

PS-MONUMENT PRESERVATION

BRETT G. BRUSATORI No. 8775

2		. *	392	W State of the sta
<del>;</del>			North -	VICINITY SKETCH
	),		) volan	
			, and the second	
			,	
	Ham La	· Ow	ase with	
,		EP	1	Pan " depth TEP
		342'		J
·		. Morse k	<u></u>	
				LEGEND
	. ,			ROW. LINE EDGE OF
£ -		1		PAVEMENT
EST: ADE: SUPV;		PERMIT SK Resteration of asp	ETCH	CO: SD: NOTIF: '
REP: LNR: CALE:	DATE DE E	PACIFIC GAS AND ELI	31	· I ONA TOP I DEVI

(90)

Prof. Sec.			And the second s		Charles State Stat	A CONTRACTOR OF THE CONTRACTOR	And the second s	Section of the second section of the section of the second section of the section o
NPH (2)	Dimension A/B/C ADVANCE WARNING SIGN SPACING (5)	Dimension L MERGING TAPER LENGTH	Dimension L/2 Skifting Taper Length	Dimension L/3 MINIMUM SHOULDER TAPER	Dimension "E" BUFFER SPACE (4-A) and FLAGGER STATION STOPPING SIGHT DISTANCE (4-B) (0%) (-3%) (-6%)	RAXIMUM CHANNELIZER TAPER SPACING (3)	MAYINUM CNANNELIZER YANGENT SPACING (3)	MAXIMUM CHANNELIZER CONFLICT SPACING (6)
I	Į.	A	7	ñ	ft	1	Ų	ij
25	100	125	9	45	(155) (160) (165)	25	020	12
30	250	180	06	09	(200) (205) (215)	30	98	15
35	250	245	125	58	(250) (260) (275)	35	20	<i>L</i> 1
40	250	320	160	110	(305) (315) (335)	40	08	20
<del>م</del>	350	540	270	180	(360) (380) (400)	<del>ل</del> م ت	Ş	22
20	350	900	300	200	(425) (450) (475)	20	8	25
55	200	099	330	220	(495) (520) (555)	20	100	25
09	200	720	360	240	(570) (600) (640)	50	80	25
65	200	780	390	260	(645) (685) (730)	20	100	25
<b>(</b> 0)	Work on Freeways	sand Expressways	shall meet the Calt	rans Standard Pla	Work on Freeways and Expressways shall meet the Caltrans Standard Plans and Standard Specification requirements.	lon requirements.		
(2)	Posted Speed or o	bserved operating	Posted Speed or observed operating speed (whichever is greater).	s greater).				
(3)	Chamelizer spacir	ng shall be reduced	Charmelizer spacing shall be reduced by half at areas where v	here work is taking	work is taking place on curves or areas of head-on conflict	ıf head-on conflict.		
(4-A)	Buffer space may	be inserted in low-s	peed urban areas	and should be insu	Buffer space may be inserted in low-speed urban areas and should be inserted in high-speed urban and rural areas	nd rural areas.		
(4-B)	The Stopping Sigh	it Distance should €	mable Road Users	to see the Priman	The Stopping Sight Distance should enable Road Users to see the Primary Flagger Station and safely stop.	clobs		
(9)	Sign spacing in rur	Sign spacing in rural areas should be 500 ft.	500 ft.	-				300 100
9	- Table 6F-101(CA)							
		TO STATE OF THE PROPERTY OF TH						

Figure 6H-6. Shoulder Work with Minor Encroachment (TA-6)

