



COUNTY OF SAN JOAQUIN

DEPARTMENT OF PUBLIC WORKS
P.O. BOX 1810-1810 E. HAZELTON AVENUE
STOCKTON, CALIFORNIA 95201
(209) 468-3000
FAX # (209) 468-9324

Permit No: PS-1902237
Date Issued: 07/03/2019
Start Date: 07/03/2019
Exp. Date: 09/01/2019
Project No: PWP730079
Quad:

UE/CR/PM NO:A01JGF6

ENCROACHMENT PERMIT

To: AT & T - FRESNO
5555 E. OLIVE RM#300III
FRESNO, CA 93727

Encroachment Type:

Bore (up to 12 inch Dia)	Trench		
--------------------------	--------	--	--

Location:

S/S MARIPOSA RD 630' W/O CARPENTER RD

In compliance with your request of 07/03/2019, permission is hereby granted to do work in County right-of-way as shown on attached application and subject to all the terms, conditions and restrictions written below or printed as general or special provisions on any part of this form. See reverse side and attached sheet, if any.

Trench excavations for service connections will not be permitted within ten feet (10') of pavement centerline unless otherwise approved by the Director. Surface of trench patches shall match in kind and be smooth and even with that of abutting surface. Special attention shall be given to depth of utilities through roadside area in anticipation of future drainage facilities, road profile and/or frontage development. All underground utility facilities are to be established and accurately dimensioned on sketches from surveyed centerline of road right of way, or from right of way (border) lines.

Permittee shall call the Department of Public Works, Field Engineering Division (Permit Inspections) at (209)953-7421 at least forty-eight hours prior to beginning any work within the County right of way. All work performed under this permit shall conform to the rules and regulations pertaining to safety established by the California Division of Industrial Safety and Cal-OSHA.

The jobsite shall be kept in a safe condition at all times by the daily removal of any excess dirt or debris which might be a hazard to either pedestrian or automobile traffic. All necessary traffic convenience and warning devices and personnel shall be provided, placed and maintained by and at the sole expense of the Permittee in accordance with the latest edition of the CALTRANS Manual of Traffic Control.

After completion of the work permitted herein, all debris, lumber, barricades, or any excess material shall be removed and the jobsite left in a neat workmanlike manner. Immediately following completion of construction permitted herein, Permittee shall fill out and mail notice of completion (see attached post card) provided by Grantor.

Special Comments:

Traffic Control Per MUTCD

FORMS: SS/WW, R-29

Est. Permit Fee: \$1,486.00

KRIS BALAJI, Director
Department of Public Works

WHITE -Permittee
GOLDENROD -PWD Central File
YELLOW -Field Inspection
PINK -Permit Section

By:


Permit Section

ENCROACHMENT PERMIT GENERAL PROVISIONS

13-1

1. This permit is issued under and subject to all laws and ordinances of agencies governing the encroachment herein permitted. See the following references:

STREETS AND HIGHWAYS CODE

1. Division 1, Chapter 3
2. Division 2, Chapter 2, Section 942
3. Division 2, Chapter 4, Section 1126
4. Division 2, Chapter 5.5 and Chapter 6

SAN JOAQUIN COUNTY ORDINANCES NUMBERED: 324, 441, 648, 662, 672, 695, 700, 860, 892, 3359, and 3675.

2. It is understood and agreed by the Permittee that the performance of any work under this permit shall constitute an acceptance of all the provisions contained herein and failure on the Permittee's part to comply with any provision will be cause for revocation of this permit. Except as otherwise provided for public agencies and franchise holders, this permit is revocable on five days notice.
3. All work shall be done subject to the supervision of and the satisfaction of the grantor. The Permittee shall at all times during the progress of the work keep the County Highway in as neat and clean condition as is possible and upon completion of the work authorized herein, shall leave the County Highway in a thoroughly neat, clean and usable condition.
4. The Permittee also agrees by the acceptance of this permit to properly maintain any encroachment structure placed by the Permittee on any part of the County Highway and to immediately repair any damage to any portion of the highway, which occurs as a result of the maintenance of the said encroachment structure, until such time as the Permittee may be relieved of the responsibility for such maintenance by the County of San Joaquin.
5. The Permittee also agrees by the acceptance of this permit to make, at its own expense, such repairs as may be deemed necessary by the County Department of Public Works.
6. It is further agreed by the Permittee that whenever construction, reconstruction or maintenance work upon the highway is necessary, the installation provided for herein shall, upon request of the County Department of Public Works, be immediately moved or removed by and at the sole expense of the Permittee.
7. No material used for fill or backfill in the construction of the encroachment shall be borrowed or taken from within the County right of way.
8. All work shall be planned and carried out with as little inconvenience as possible to the traveling public. No material shall be stacked within eight feet (8') of the edge of the pavement or traveled way unless otherwise provided herein. Adequate provision shall be made for the protection of the traveling public. Traffic control standards shall be utilized including barricades; approved signs and lights; and flagmen, as required by the particular work in progress.
9. The Permittee, by the acceptance of this permit, shall assume full responsibility for all liability for personal injury or damage to property which may arise out of the work herein permitted or which may arise out of the failure of the part of the Permittee to properly perform the work provided under this permit. In the event any claim of such liability is made against the County of San Joaquin or any department, official or employee thereof, the Permittee shall defend, indemnify, and hold each of them harmless for such claim.
10. All backfill material is to be moistened as necessary and thoroughly compacted with mechanical means. If required by the County Director of Public Works, such backfill shall consist of gravel or crushed rock. The Permittee shall maintain the surface over structures placed hereunder as may be necessary to insure the return of the roadway to a completely stable condition and until relieved of such responsibility by the County Department of Public Works. Wherever a gravel, crushed rock or asphalt surface is removed or damaged in the course of work related to the permitted encroachment, such material shall either be separately stored and replaced in the roadway as nearly as possible in its original state or shall be replaced in kind, and the roadway shall be left in at least as good a condition as it was before the commencement of operations of placing the encroachment structure.
11. Whenever it becomes necessary to secure permission from abutting property owners for the proposed work, such authority must be secured by the Permittee prior to starting work.
12. The current and future safety and convenience of the traveling public shall be given every consideration in the location and methods of construction utilized.
13. The Permittee is responsible for the preservation of survey monuments located within the area of work herein permitted. Prior to the start of construction, survey monuments that potentially may be disturbed shall be located and referenced by a Licensed Land Surveyor, and a Corner Record filed with the County Surveyor. Any Survey Monuments disturbed during the course of construction shall be reestablished by a Licensed Land Surveyor and another Corner Record filed with the County Surveyor. (Land Surveyors' Act Section 8771)
14. Prior to any excavation, the Permittee shall notify USA North (Underground Service Alert of Northern California and Nevada) at 811 or 800-227-2600 forty-eight (48) hours in advance.

APPLICATION FOR ENCROACHMENT PERMIT

PLEASE PRINT:

Date ~~04/23/19~~ 5/29/2019

To: San Joaquin County
Department of Public Works

AT&T / VCC PERMITS DESK
(Applicant Name)

5555 E. Olive Ave
(Mailing Address)

Fresno, CA 93727
(City, State, Zip Code)

(559) 454-4900 g26977@att.com
(Area Code - Telephone Number)

OFFICE USE ONLY		
JOB #	730079	REF #
APN		CR #
EXP. DATE		
VALID	TO	DRIVEWAYS:
STREET		*
AREA	QUAD	*
TYPE		*
FORMS		
NOTES		

Sketch (Detailed plans may be submitted)

A COPY OF THE TRAFFIC CONTROL PLAN IS SUBMITTED WITH THIS PERMIT;
SEE ATTACHMENTS

Resubmital
Please Expedite !!!

The undersigned hereby applies for permission to excavate, construct and/or otherwise encroach on County Highway Right-of-Way on the SOUTH side of E MARIPOSA RD approximately 630 feet mile WEST of CARPENTER RD, by performing the following work (description of work):
AERIAL PLACEMENT INVOLVING (2) POLES & (2) AERIAL STREET CROSSING OVER E MARIPOSA RD & CARPERNTER RD. S/S MARIPOSA RD, 460' N/W/O/C/L/O CARPENTER RD: PLACE POLE AND GROUND BED. N/S CARPENTER RD, 365' E/O/C/L/O E MARIPOSA RD: PLACE POLE AND GROUND BED. THE ASSOCIATED TRAFFIC CONTROL PLAN IS SUBMITTED WITH THIS PERMIT. PLEASE SEE ATTACHED PERMIT DRAWINGS FOR AT&T JOB# A01JGF6.

Work will commence on or about ~~5-1-19~~ 7/01/2019 for approximately 5 days.

I, the undersigned, certify that I am the owner of the respective property, or am qualified to represent the owner and agree to do the work described above in accordance with the rules and regulations of San Joaquin County and subject to inspection and approval.

Rhonda Potts for AT&T Engineering Administrator
Signature of Applicant - Title

~~4/24/2019~~ 5/29/2019
Date

RECEIVED
SAN JOAQUIN COUNTY

2019 MAY 30 PM 1:26

DEPT OF PUBLIC WORKS

ENCROACHMENT PERMIT APPLICATION REQUIREMENTS:

A completed San Joaquin County Encroachment Permit application signed and dated. Application can be found on the Public Works website at: <https://www.sjgov.org/departments/pwk/permits>

- Application must include work schedule; dates and all pertinent information.
- A completed "Survey Monument Preservation Form", which can be found on the Public Works website at: <https://www.sjgov.org/departments/pwk/permits>
- Four (4) sets of traffic control plans prepared in accordance with the latest edition of the California Manual on Uniform Traffic Control Devices (CA MUTCD). The CA MUTCD can be found online at: <http://www.dot.ca.gov/trafficops/engineering/>
- Four (4) sets of improvement plans (11" x 17", if clearly legible, otherwise 24" x 36") with the following information:
 - a. Site Plan (Vicinity Map)
 - b. Right-of-way lines, centerline, edge of pavement, curb, gutter and sidewalk and all existing utilities labeled and dimensioned.
 - c. Type of work and location clearly identified. Must include dimensions relative to the right-of-way, centerline, edge of pavement, etc.
 - d. Typical cross-sections.
 - e. Typical back-fill detail per the San Joaquin County Public Works Standard R-29 (use San Joaquin County Standard Specifications and Special Provisions as a guide located on the Public Works website).
 - f. Show/label City/County/State limit line near work area, where applicable.
 - g. North Arrow and Scale. 1"=20' Scale min.

Note:

1. Complete submittals shall be mailed or hand-delivered to the San Joaquin County Public Works office (attn.: encroachment permit counter).



SAN JOAQUIN
COUNTY
Greatness grows here.

**Department of Public Works**

Kris Balaji, Director of Public Works

Fritz Buchman, Deputy Director/Development

Michael Selling, Deputy Director/Engineering

Jim Stone, Deputy Director/Operations

Kristi Rhea, Manager of Strategic Initiatives

Acknowledgement of Monument Preservation

I, MICHAEL HALTERMAN, a duly Licensed Land Surveyor or a Professional Engineer
(Please print)

authorized to perform Land Surveying in the State of California, Registration No. LS 8040,

hereby acknowledge and accept all responsibility for the monument preservation as required

per Section 8771(a-f) of the Business and Professions Code within the bounds of the

construction activity permitted by San Joaquin County Permit No. _____.

I further acknowledge that I am hereby responsible for the Acknowledgement of Monument
Preservation prior to final acceptance of the construction activity.

Signature

Seal

19 APRIL 2019

Date



PS-MONUMENT PRESERVATION

= construction location

SCALE: 1" = 150'

MAP OF SURVEY

PORTION OF
LOTS 1 & 2 CLARKADOTA FIG
PLANTATIONS, BEING IN SECS.
58 & 68 C.M. WEBER GRANT
SAN JOAQUIN COUNTY,
CALIFORNIA

R.W. SIEGFRIED & ASSOCIATES
STOCKTON, CALIFORNIA
CIVIL ENGINEERS
JUNE 1974

BASIS OF BEARINGS:

The eastern line of Mariposa Road, which bears
N 67° 40' 30" W as shown on the Map of Survey filed for record
in Book 24 of Surveys, Page 24, San Joaquin County Records

MONUMENTS SET:

Iron Pins, 3/4" in diameter, 30" long with brass tag attached
and stamped "R.C.E. 8189", shown thus: _____

LEGEND:

Maps of Survey, along with the Volume and Page shown
hereon, as filed in Book of Surveys, San Joaquin County
Records, are shown thus: F. S. for Filed Survey.

SURVEYOR'S CERTIFICATE:

This map correctly represents a survey made by me or under
my direction in conformance with the requirements of the Land
Surveyor's Act of the request of William J. Ward
in Aug. 1974.

Robert W. Siegfried
Registered Civil Engineer No. 8189

COUNTY SURVEYOR'S CERTIFICATE:

This map has been examined for conformance with the requirements
of the Land Surveyor's Act this 15 day of Aug. 1974.

William J. Ward
William J. Ward, County Surveyor

I HEREBY CERTIFY that this record of survey of land
complies with the provisions of the Subdivision Map Act,
Chapter 2 (commencing with Section 11500) of Part 2,
Division 4 of the Business and Professions Code, and any
applicable local ordinance enacted pursuant thereto.

Dated 8/15/74

William J. Ward
William J. Ward, County Surveyor


RECORDER'S CERTIFICATE:

Filed this 20 day of Aug. 1974 at 10
A.M. in Book 24 of Surveys at Page 24, at the request of
Robert W. Siegfried.

Fee \$ 0.00

George H. Chapman
County Recorder
Deputy

NOTE: Refer to Division of Land Map
No. 145111



● = construction location

Basis of Bearings: Carpenter Road, formerly Grady Avenue, as per Subdivision No. 2, Clarkdale Pig Plantations, filed in Book of Maps, Vol. 12, Page 76, San Joaquin County Records.

Measurements taken from Plans, 1"=60' and 30"=60', metal tape attached and stamped M.E. 1014.

This map correctly represents a survey made by me, in order my direction in accordance with the requirements of Chapter 12 of Division 3 of the Business and Professions Code, at the request of F.J. Lapcia.

Dated April 2, 1963


Steve H. Wilkerson
Civil Engineer and



This map has been examined by me for conformance with the requirements of Chapter 12 of Division 3 of the Business and Professions Code.

Dated April 30, 1963

Blomont G. Pearce
County Surveyor




Filed for record May 15, 1963, at 1:25 P.M. in Book of Surveys Vol. 12, at Page 64, San Joaquin County Records, at the request of Steve H. Wilkerson, No. 23271

Steve H. Wilkerson
Civil Engineer


By _____
County

MAP OF SURVEY
PROPERTY OF F. J. LAPCIA
IN LOT 29, SUBDIVISION NO. 2,
CLARKDALE PIG PLANTATIONS
IN SEC 24, CH. WICKER GRANT
SAN JOAQUIN COUNTY, CALIFORNIA
Chas. H. Wilkerson - Geo. C. Hennitz
Civil Engineers
April 1963. Scale 1"=60'



NOTES:

1. New pavement shall be 1" thicker than existing pavement, minimum of 0.25 Ft. New base shall be 1" thicker than existing base, min of 0.50 Ft.
2. Select native material or imported granular material as approved by the Director of Public Works. Backfill with materials equal to or better than the existing pavement and base in quality.
3. Relative compaction of materials shall be tested in accordance with the State of California, Dept. of Transportation Testing Manuals, test method No. California 216 or 231.
4. All existing pavement shall be neatly cut to line prior to trench excavation.
5. Jetting or ponding will be permitted within the street right-of-way with a 3 year bond, when approved by the Director of Public Works.
6. When shown by soil composition and compactability, ninety percent (90%) compaction may be used, when approved by the Director of Public Works.
7. Special bedding and backfill requirements may be shown on the plans or specified in the special provisions.



TYPICAL TRENCH BACKFILL

COUNTY OF SAN JOAQUIN
DEPARTMENT OF PUBLIC WORKS

Approved by:

Thomas M. Grew

No.	Revision	Description	Date

Date: DEC 2014

Std. Dwg. No.

R-29

GENERAL PROVISIONS

GOVERNING INSTALLATION OF SUBSURFACE STRUCTURES AND PIPELINES WITHIN COUNTY ROAD RIGHTS-OF-WAY

PUBLIC CONVENIENCE AND SAFETY:

- A. Before obstructing any private driveway entrance or County road traveled way with a trench, spoil bank, equipment or other barrier permitted for any prolonged period of time, the Permittee shall notify the known users of the respective thoroughfare(s) involved, and shall provide access for vehicular and pedestrian traffic to and from the road.
 - 1. Unless otherwise permitted, all work shall be conducted in such a manner that no less than one lane of the existing County road traveled way will be maintained open to public traffic during working hours in a smooth and safe riding condition(s). Two lanes shall be open after working hours.
 - 2. In cases where road closure is permitted, the permission to close the road will be granted under the condition that the Permittee notify the following persons and/or agencies of the time, the period of closure, and the detour route at least twenty-four (24) hours prior to said road closure.
 - a. The County of San Joaquin Public Works Department
 - b. The County of San Joaquin Sheriff's Office
 - c. The local postal service
 - d. The local fire district
 - e. The local school district
 - f. The local residents involved
- B. Should hazardous conditions relative to the installation operations warrant flagmen, as many capable flagmen as may be necessary shall be provided by the Permittee and stationed in advance of work to warn and direct traffic.
- C. Lights, signs and barricades shall be furnished, erected and maintained by the Permittee for the adequate warning and convenience of the public, with particular attention to be taken in this regard after dark.
- D. Any excess dirt and/or debris which might be a hazard to either automobile or pedestrian traffic, uncontrollable by lights, signs and barricades, shall be removed from the jobsite daily.

STRUCTURES:

- A. Walls of structures shall be such quality and strength that they will resist all pressures and will not crack or be deformed in such a way as to create a hazard or maintenance problem at any time. Therefore, the minimum structural requirements for concrete pipe placed under county road rights-of-way shall conform to the following American Association of State Highway and Transportation Officials (AASHTO) designations.
 - 1. For concrete pipe up to and including thirty-three inches (33") inside diameter, extra strength concrete conforming to AASHTO Designation M 170M.
 - 2. For concrete pipe thirty-six inches (36") inside diameter and larger, reinforced concrete pipe conforming to AASHTO Designation M 170M Class III.
 - 3. Plastic pipe conforming to AASHTO Designation M294.
- B. All concrete pipe joints with County road rights-of-way shall be sealed against leakage and/or infiltration with rubber gasket in conformance with Section 65-1.06 of the California Standard Specifications, or with other methods as may be permitted under the Special Provisions.
- C. Cast-in-place concrete pipe, vitrified clay pipe, spiral welded steel pipe, or corrugated aluminum alloy pipe shall not be installed within the County road rights-of-way unless specifically so stated in the Special Provisions, and only under the conditions as provided.
- D. All structures to be buried within the County rights-of-way shall be set at such elevations as to allow minimum coverage of thirty inches (30") to the centerline of the roadways and twelve inches (12") at the bottoms of borrow ditches each side of the roadways. The depths of structures shall be established below a flat plane extending across the rights-of-way, no part of which shall extend above the elevations stated above; manholes, lampholes, valves, etc. not included. Future surface elevations shall be anticipated as nearly as possible and structure elevations shall be established for future adjustments accordingly.
- E. The County hereby reserves the right to specify in the Special Provisions the gage and surface treatment of any galvanized corrugated metal pipe that is to be installed.
- F. All longitudinal utility facilities are to be established (and dimensioned on sketches) from surveyed centerline of road right-of-way, not from right-of-way (border) lines.

REPAIRS OF THE COUNTY RIGHT-OF-WAY:

- A. All excavations shall be backfilled and compacted immediately after work therein has been completed.
- B. Trenched shall not be left open farther than 300 feet in advance of pipe laying operations, or 200 feet to the rear thereof, unless otherwise permitted by the Engineer.
- C. Unless otherwise permitted under the Special Provisions, backfill shall be placed and mechanically compacted in such a manner that the relative compaction throughout the entire fill within the County road right-of-way shall conform to the percentages of compaction as shown on the Trench detail.
- D. Backfill material shall be placed in horizontal uniform layers not to exceed in thickness, before compaction, 0.67 foot in the bedding region, one -foot where 90% compaction is required, and two-feet where 80% compaction is required.
- E. No portion of the excavation(s) shall be compacted by ponding or jetting unless a maintenance bond is provided.
- F. Gravel backfill material shall be utilized only where specifically so stated on the face of the permit. It shall be compacted by means of a high-frequency internal vibrator, the compactor to be a size and type approved by the Engineer. Points of compaction shall not be greater than 18" centers and to the full depth of the lift.
- G. All pavements, curbs, gutters, sidewalks, borrow ditches, pipes, head walls, road signs, trees, shrubbery, and/or other permanent road facilities impaired by or as a result of construction operations at the construction site(s) occupied by materials and/or equipment, shall be restored immediately upon backfilling of the excavation to the original grades and cross sections, and to a condition as good as, or better than existing prior to construction.
- H. All surfacing materials of roadways and driveway approaches cut or damaged by or as a result of construction operations, shall be replaced within ONE WEEK following the backfilling of excavation, weather permitting, with compacted layers of surfacing materials at least as thick as the existing, and no less than two inches (2") of asphalt concrete over six inches (6") of aggregate base, both as specified below.
 - 1. Asphalt Concrete: Combined mineral aggregate shall conform to the quality and gradation requirements for Type "A" one-half inch (1/2) maximum aggregate, coarse or medium gradation as specified in Section 39 of the California Standard Specifications. The bituminous binder to be mixed with mineral aggregate shall be paving asphalt having (Grade PG 64-10), unless otherwise directed by the Engineer. Placement of asphalt concrete surfacing shall conform to the applicable provisions of Section 39 of the California Standard Specifications.
 - 2. Aggregate Base: Combined mineral aggregates shall conform to the quality and the grading for three-quarter inch (3/4") maximum size aggregate Class 2 Aggregate Base specified in Section 26 of the California Standard Specifications.
- I. Before acceptance of repairs to the County road rights-of-way, all unsightly and detrimental dirt, dust and/or debris shall be removed and the construction areas left in a neat and presentable condition(s).
 - 1. If necessary, County road traveled way and driveway pavements shall be washed with water to remove dirt and dust.
 - 2. Driveway approaches and field entrance pavements damaged by equipment or spoil banks shall be repaired as directed by the Engineer.
- J. Upon request by the County, any settlement, sagging of surface, or cracking of pavement shall be repaired immediately by and at the sole expense of the Permittee for a period of one year following acceptance of the work.

SPECIAL PROVISIONS

Winter Weather Utility Work

1. **SUPERVISION:** The utility company (**permittee**) shall furnish full-time supervision of all work to insure compliance with the permit provision.
2. **START OF WORK:** No work within the County right-of-way shall be started until the utility company representative has made an evaluation of weather conditions and has determined the work can be accomplished under the provisions of the permit.
3. **CLEAN PAVEMENT:** Dirt and mud shall not be deposited on the pavement outside the area of work, and if inadvertently tracked onto the road travel way shall be removed immediately.
4. **DAILY RESTORATION:** Private driveways and road intersections shall be restored daily.
5. **WEATHER-TIGHT CONDITIONS:** All trenches shall be filled and compacted, ditches and other drainage facilities regarded and opened, and the entire work area restored to weather-tight condition prior to any rain.

CONSTRUCTION NOTES

1 DIG 2'X2' PIT
& PL. NEW POLE

ISSUE	DATE
1	03/14/19

LEGEND

⊗	POLE
FOC	FACE OF CURB
—	PROPOSED CONDUIT
R/W	RIGHT OF WAY
℄	CENTERLINE
BOS	BACK OF SIDEWALK
[S]	STOP SIGN
CSW	CONCRETE SIDEWALK
EOP	EDGE OF PAVEMENT
○	FENCE

Call USA @ 811
48hrs prior to start of work

SAFETY NOTE


WORK AREA WILL INCLUDE LANE
CLOSURE ON ROAD WITH VERY HIGH
TRAFFIC VOLUME. PLEASE PROVIDE
COMPLETE WORK AREA PROTECTION.

M.O.P REQUIRED
CATEGORY - 3

FOLLOW PROCEDURES AS DETAILED IN
NORTHERN SECTOR PLAN FOR PROTECTION
OF UNDERGROUND AND BURIED CABLE
M.O.P. DATED

GENERAL NOTES:

1. CONTRACTOR SHALL REQUEST LOCATION OF
UNDERGROUND FACILITIES BY USA
2. CONTRACTOR WILL COMPLY WITH ALL
SAN JOAQUIN COUNTY REGULATIONS FOR SPLICE
PIT & SURFACE COMPACTION
3. CONTRACTOR WILL RETURN WORK AREA BACK
TO ORIGINAL OR BETTER CONDITION PRIOR TO
START OF WORK
4. MAINTAIN 36" MINIMUM COVER



CHC Consulting
1845 W. Orangewood Ave. , Suite 300
Orange, CA 92868
(949) 250-0004 / FAX (949) 250-0006

GEO / CD UE73
EXCHANGE: SKTNCA01
ENG. JORGE MONZON
TEL: 559-739-6134 ENG.ARC VOKDEEB00
TYPE OF CONST. POLE PLACEMENT
RD /EST NO. A01JGF6
DWG 1 OF 2 P

EXCAVATION DATA

OWNER	ASPHALT	DIRT	CONCRETE
COUNTY OF SAN JOAQUIN	_____	(DIG PIT) 2'X2'=4 SQ FT	_____

CONSTRUCTION NOTES

1 DIG 2'X2' PIT
& PL. NEW POLE

ISSUE	DATE
1	03/14/19

LEGEND

⊗	POLE
FOC	FACE OF CURB
—	PROPOSED CONDUIT
R/W	RIGHT OF WAY
CL	CENTERLINE
BOS	BACK OF SIDEWALK
[S]	STOP SIGN
CSW	CONCRETE SIDEWALK
EOP	EDGE OF PAVEMENT
○	FENCE

Call USA @ 811
48hrs prior to start of work

SAFETY NOTE


WORK AREA WILL INCLUDE LANE
CLOSURE ON ROAD WITH VERY HIGH
TRAFFIC VOLUME. PLEASE PROVIDE
COMPLETE WORK AREA PROTECTION.

M.O.P REQUIRED CATEGORY - 3

FOLLOW PROCEDURES AS DETAILED IN
NORTHERN SECTOR PLAN FOR PROTECTION
OF UNDERGROUND AND BURIED CABLE
M.O.P. DATED

GENERAL NOTES:


1. CONTRACTOR SHALL REQUEST LOCATION OF
UNDERGROUND FACILITIES BY USA
2. CONTRACTOR WILL COMPLY WITH ALL
SAN JOAQUIN COUNTY REGULATIONS FOR SPLICE
PIT & SURFACE COMPACTION
3. CONTRACTOR WILL RETURN WORK AREA BACK
TO ORIGINAL OR BETTER CONDITION PRIOR TO
START OF WORK
4. MAINTAIN 36" MINIMUM COVER



SCALE

CHC Consulting
1845 W. Orangewood Ave. , Suite 300
Orange, CA 92668
(949) 250-0004 / FAX (949) 250-0005

GEO / CD UE73
EXCHANGE: SKTNCA01
ENG. JORGE MONZON
TEL: 559-739-6134 ENG.ARC VOKDEEB00
TYPE OF CONST. POLE PLACEMENT
RD /EST NO. A01JGF6
DWG 2 OF 2 P



EXCAVATION DATA

OWNER	ASPHALT	DIRT	CONCRETE
COUNTY OF SAN JOAQUIN	—	(DIG PIT) 2'X2'=4 SQ FT	—

SIGN LEGEND

ROAD WORK AHEAD
W20-1

ROAD CLOSED AHEAD
W20-3

DETOUR AHEAD
W20-2

RIGHT LANE CLOSED AHEAD
C20(CA)(R)

LEFT LANE CLOSED AHEAD
C20(CA)(L)

CENTER LANE CLOSED AHEAD
W9-3

BIKE LANE CLOSED AHEAD
C20(CA)(BIKE)

W4-2(R)
W4-2(L)

LANE CLOSED
C30 (CA)

BIKE LANE CLOSED
C30(BIKE)

ONE LANE ROAD AHEAD
W20-4

BE PREPARED TO STOP
W3-4

RAMP CLOSED AHEAD
W20-3

SPEED LIMIT 35
W3-5

NARROW LANE
C12(CA)

ROAD NARROWS
W5-1

W12-1

W6-3

W1-4(L)
W1-4(R)

W4-1

W21-1a

C9A (CA)

C27(CA)

W11-1

SHOULDER WORK
W21-5

RIGHT SHOULDER CLOSED AHEAD
W21-5bR

RIGHT SHOULDER CLOSED 1000 FT
W21-5b

SHOULDER CLOSED
C30A

R3-1

R3-2

R3-4

R3-18

R5-6

R9-3

STOP
R1-1

YIELD
R1-2

DO NOT ENTER
R5-1

SLOW
SLOW PADDLE

RIGHT LANE MUST TURN RIGHT
R3-7(R)

LEFT LANE MUST TURN LEFT
R3-7(L)

ROAD CLOSED
R11-2

RAMP CLOSED
R11-2

ROAD CLOSED TO THRU TRAFFIC
R11-4

BEGIN RIGHT TURN LANE
YIELD TO BIKES
R4-4

SHARE THE ROAD
W16-1P

BIKE MAY USE FULL LANE
R4-11

BUSES ONLY
SPCL

KEEP RIGHT
R4-7a

KEEP LEFT
R4-8a

R3-6(R)
R3-6(L)

R4-7

R4-8

R3-5R
ONLY

R60B(CA)

SIDEWALK CLOSED
R9-9

SIDEWALK CLOSED AHEAD
CROSS HERE
R9-11(L)
R9-11(R)

SIDEWALK CLOSED
CROSS HERE
R9-11a(L)
R9-11a(R)

SIDEWALK CLOSED
USE OTHER SIDE
R9-10

END ROAD WORK
G20-2

W1-6(R)
W1-6(L)

W1-7

SC3 (CA)

END DETOUR
M4-8a

DETOUR
M4-9(L)
M4-9(R)
M4-9(S)

M4-10(L)
M4-10(R)

ON RED
R13A

ON RED
R13B

DO NOT STOP ON TRACKS
R8-8

SYMBOL LEGEND

CHANNELIZING DEVICE/CONE

CHANNELIZING DEVICE W/ SIGN

TYPE I BARRICADE W/ SIGN

EXISTING SIGN

SIGNALIZED INTERSECTION

TYPE III BARRICADE W/SIGN(5'H x 4'W)

TYPE II BARRICADE W/SIGN(3'H x 2'W)

HIGH LEVEL WARNING DEVICE

FLASHING ARROWBOARD

T.A.N.S.A.T.

TYPE I BARRICADE

TYPE II BARRICADE

CERTIFIED FLAGGER

PORTABLE FLASHING BEACON

T.A.N.S.

AERIAL CABLE

SPLICE BOX

EXISTING STRIPING-DOUBLE YELLOW

EXISTING STRIPING

CHANGEABLE MESSAGE SIGN (CMS)

TRENCHING

HAND HOLE

BORE PIT

POWER POLE

MANHOLE

EXISTING DRIVEWAY

WORK ZONE (ACTIVITY AREA)

DIRECTION OF TRAVEL

EXISTING LANE FLOW STRIPING

WORK VEHICLE

GENERAL TRAFFIC CONTROL NOTES:

1. THE CONTRACTOR IS RESPONSIBLE FOR PROMPTLY RESTORING THE ROAD BACK TO SATISFACTORY CONDITION WHICH INCLUDES, BUT IS NOT LIMITED TO, PAVING, STRIPING, MARKINGS, SIGNAGE, AND LOOP DETECTION. ALL PLANS SHALL BE IN ACCORDANCE WITH 2014 CAMUTCD.
2. THE AGENCY RESERVES THE RIGHT TO OBSERVE THESE TRAFFIC CONTROL PLANS IN OPERATION AND TO MAKE CHANGES AS FIELD CONDITIONS WARRANT.
3. TRENCHES SHALL BE BACKFILLED OR STEEL-PLATED DURING NON-WORK HOURS. STEEL PLATES SHALL HAVE AN ASPHALT RAMP ON ALL EDGES, SECURELY SUPPORTED SO THEY WON'T ROCK AND A SIGN POSTED NEAR THE PLATES IDENTIFYING THE CONTRACTOR'S NAME AND 24 HOUR EMERGENCY TELEPHONE NUMBER. ALL DIRT, DUST, AND DEBRIS SHALL BE REMOVED FROM THE STREET AT THE END OF EACH DAY AND AT THE END OF THE JOB. THE STREET SHALL BE KEPT IN A DRIVABLE CONDITION AT ALL TIMES.
4. ANY WORK THAT CREATES AN UNDUE SAFETY RISK OR THAT CREATES SEVERE CONGESTION WILL BE SHUT DOWN BY THE AGENCY.
5. A COPY OF ALL TRAFFIC REQUIREMENTS AND TRAFFIC CONTROL PLANS ISSUED BY THE AGENCY MUST BE KEPT ON THE JOB SITE.
6. APPROVAL OF THIS PLAN DOES NOT CONSTITUTE AN OFFICIAL PERMIT. CONTACT THE AGENCY FOR INFORMATION ON OBTAINING A PERMIT.
7. ALL TRAVEL LANES WILL TYPICALLY BE A MINIMUM OF 12 FEET WIDE, 14 FEET IF ADJACENT TO BIKE LANES, UNLESS OTHERWISE SPECIFICALLY APPROVED BY THE AGENCY.
8. FLASHING ARROW BOARDS AS REQUIRED BY THE AGENCY.
9. WARNING (W) SERIES SIGNS USED IN WORK ZONES SHALL BE BLACK ON AN ORANGE BACKGROUND.
10. CONES AND PYLONS SHALL HAVE YELLOW REFLECTORIZED SLEEVES WHEN PLACED ALONG THE CENTERLINE AND WHITE REFLECTORIZED SLEEVES ALONG THE OUTSIDE SHOULDER.
11. IF PARKING IS ALLOWED IN THE ADVANCE WORKING AREA, ADVANCE WARNING SIGNS SHALL BE MOUNTED ON HIGH LEVEL DEVICES.
12. THE CONTRACTOR SHALL POST TOW-AWAY/NO PARKING SIGNS SEVENTY-TWO (72) HOURS IN ADVANCE, WITH DAY OF WEEK, DATE, AND WORK HOURS NOTED, AND SHALL BAG PARKING METERS (WHERE APPLICABLE).
13. OPEN CUT WORK SHALL BE DONE IN __ PHASES.
14. WORKERS SHALL WEAR HARD HATS AND ORANGE VESTS AT ALL TIMES.
15. COUNTY TRANSIT DISTRICT SHALL BE NOTIFIED (5) WORKING DAYS PRIOR TO ANY WORK THAT AFFECTS BUS STOPS.
16. CONSTRUCTION SIGNS SHALL NOT OBSTRUCT SIGHT VISIBILITY AT DRIVEWAYS.
17. CONTRACTOR SHALL NOTIFY ALL LOCAL BUSINESS OWNERS/OCCUPANTS 72 HOURS IN ADVANCE PRIOR TO ANY CONSTRUCTION ADJACENT TO BUSINESSES.

JOB LOCATION:

E MARIPOSA RD.

PERMIT NUMBER:

BEGIN CROSS STREET:

FRONTAGE RD.

END CROSS STREET:

AUSTIN RD.

CONTRACTOR CONTACT INFORMATION :

SCOPE OF WORK:
MH ACCESS & AERIAL PLACEMENT & CROSSING

HOURS OF OPERATION:

START DATE:

END DATE:

DURATION:

DAYS:

TABLE 6C-1 2014 CALIFORNIA MUTCD-RECOMMENDED ADVANCE WARNING SIGN SPACING-

ROAD TYPE	DISTANCE BETWEEN SIGNS**		
	A	B	C
URBAN - 25 MPH OR LESS***	100 FEET	100 FEET	100 FEET
URBAN - MORE THAN 25 MPH TO 40 MPH***	250 FEET	250 FEET	250 FEET
URBAN - MORE THAN 40 MPH***	350 FEET	350 FEET	350 FEET
RURAL	500 FEET	500 FEET	500 FEET
EXPRESSWAY/FREEWAY	1,000 FEET	1,500 FEET	2,640 FEET

** THE COLUMN HEADING A, B, AND C ARE THE DIMENSIONS SHOWN IN FIGURES 6H-1 THROUGH 6H-46. THE A DIMENSION IS THE DISTANCE FROM THE TRANSITION OR POINT OF RESTRICTION TO THE FIRST SIGN. THE B DIMENSION IS THE DISTANCE BETWEEN THE FIRST AND SECOND SIGNS. THE C DIMENSION IS THE DISTANCE BETWEEN THE SECOND AND THIRD SIGN. (THE "FIRST SIGN" IS THE SIGN IN A THREE-SIGN SERIES THAT IS CLOSEST TO TTC ZONE. THE "THIRD SIGN" IS THE SIGN THAT IS FURTHEST UPSTREAM FROM THE TTC ZONE.)

*** POSTED SPEED LIMIT, OFF-PEAK 85TH-PERCENTILE SPEED PRIOR TO WORK STARTING, OR OTHER ANTICIPATED OPERATING SPEED IN MPH

TABLE 6C-2 2014 CALIFORNIA MUTCD-STOPPING SIGHT DISTANCE AS A FUNCTION OF SPEED ON LEVEL ROADS-(USED AS SUGGESTED LONGITUDINAL BUFFER SPACE LENGTH OR LOCATION FOR FLAGGER STATION)

SPEED* (MPH)	DISTANCE (FT)
20	115
25	155
30	200
35	250
40	305
45	360
50	425
55	495
60	570
65	645
70	730
75	820

* POSTED SPEED, OFF-PEAK 85TH-PERCENTILE SPEED PRIOR TO WORK STARTING OR THE ANTICIPATED OPERATING SPEED IN MPH

TABLE 6C-3 2014 CALIFORNIA MUTCD-TAPER LENGTH CRITERIA FOR TEMPORARY TRAFFIC CONTROL ZONE-

TYPE OF TAPER	TAPER LENGTH (L)*
MERGING TAPER	AT LEAST L
SHIFTLING TAPER	AT LEAST 0.3 L
SHOULDER TAPER	AT LEAST 0.33 L
ONE LANE, TWO-WAY TRAFFIC TAPER	SOFT MINIMUM, 100FT MAXIMUM
DOWNSTREAM TAPER	SOFT MINIMUM, 100FT MAXIMUM

TABLE 6C-4 2014 CALIFORNIA MUTCD-FORMULAS FOR DETERMINING TAPER LENGTH-

SPEED LIMIT (S) (MPH)	TAPER LENGTH (L) (FEET)
40 MPH OR LESS	$L = \frac{WS}{S}$
45 MPH OR MORE	$L = WS$

WHERE: L= TAPER LENGTH IN METERS (FEET)
W= WIDTH OF OFFSET IN METERS (FEET)
S= POSTED SPEED LIMIT, OR OFF-PEAK 85TH-PERCENTILE SPEED PRIOR TO WORK STARTING, OR THE ANTICIPATED OPERATING SPEED IN KM/H (MPH)

COUNTY OF: SAN JOAQUIN

TRAFFIC CONTROL PLAN

PLANS ACCEPTED BY:

R.C.E.

DATE:

EXP. DATE:

CHC Consulting
1845 W. Orangewood Ave., Suite 300, Orange, CA 92868
(949) 250-0004 / FAX (949) 250-0006


PLANS PREPARED BY:
NAME: JANESHWAR SINGH
PHONE: (949) 250-0004
DATE: 03-12-19 REVISION DATE: N/A

JOB NUMBER A01JGF6
SCALE: N/A
PAGE: COVER SHEET

*-MH #2727 ACCESS
WORK AREA 1 OF 2
PHASE 1 OF 1*



ISSUE	DATE
1	03-12-19



WORK AREA















E Mariposa Rd

Ryder Truck Rental

Jim Dyer's Chevy Classics

E 1st St

N

- ## LEGEND
- | | |
|---|---|
|  | = PORTABLE FLASHING BEACON (P.F.B.) |
|  | = TYPE III BARRICADE W/SIGN (5'H x 4'W) |
|  | = TYPE II BARRICADE W/SIGN (3'H x 2'W) |
|  | = 28" (11cm) TRAFFIC CONES W/ 13" (5cm) REFLECTIVE SURFACE FOR DAY/NIGHT USE OR DELINEATORS IF DAY USE ONLY |
|  | = TRAFFIC CONE WITH CLIP ON SIGN |
|  | = TYPE I W/ SIGN |
|  | = EXISTING SIGN |
|  | = SIGNALIZED INTERSECTION |
|  | = FLASHING ARROWBOARD |
|  | = HIGH LEVEL WARNING DEVICE (FLAGTREE) |
|  | = FLAGGER |
| TANSAT | = TOW AWAY NO STOPPING ANY TIME |
|  | = EXISTING DRIVEWAY |
|  | = WORK ZONE (ACTIVITY AREA) LIMITS |
|  | = DIRECTION OF TRAFFIC |



**MAINTAIN DRIVEWAY ACCESS
AT ALL TIMES**

PHASE 1 OF 1

TYPE OF CONSTRUCTION:
MH #2727 ACCESS

JOB NUMBER: A01JGF6

PAGE: TC-1 OF TC-5


SCALE:
1:60



ISSUE	DATE
1	03-12-19

E MARIPOSA RD. 

**E MARIPOSA RD. & CARPENTER RD.
-AERIAL PLACEMENT
WORK AREA 2 OF 2
PHASE 1 OF 4**




FLAGGERS SHALL REMAIN IN COMMUNICATION VIA RADIO AT ALL TIMES.

ACCESS TO DRIVEWAY MUST BE MAINTAINED AT ALL TIMES.

CONTACT PROPERTY OWNER(S) 72 HOURS PRIOR TO START OF WORK.

MAINTAIN DRIVEWAY ACCESS AT ALL TIMES

LOCATION MAP



- LEGEND**
- = PORTABLE FLASHING BEACON (P.F.B.)
 - = TYPE III BARRICADE W/SIGN (5'H x 4'W)
 - = TYPE II BARRICADE W/SIGN (3'H x 2'W)
 - = 28" (11cm) TRAFFIC CONES W/ 13" (5cm) REFLECTIVE SLEEVE FOR DAY/NIGHT USE OR DELINEATORS IF DAY USE ONLY
 - = TRAFFIC CONE WITH CLIP ON SIGN
 - = TYPE I W/SIGN
 - = EXISTING SIGN
 - = SIGNALIZED INTERSECTION
 - = FLASHING ARROWBOARD
 - = HIGH LEVEL WARNING DEVICE (FLAGTREE)
 - = FLAGGER
 - = TANSAT
 - = TOW AWAY NO STOPPING ANY TIME
 - = EXISTING DRIVEWAY
 - = WORK ZONE (ACTIVITY AREA) LIMITS
 - = DIRECTION OF TRAFFIC


PHASE 1 OF 4	
TYPE OF CONSTRUCTION: AERIAL PLACEMENT	
JOB NUMBER: A01JGF6	
PAGE: TC-2 OF TC-5	SCALE: 1:60

E MARIPOSA RD. & CARPENTER RD.

AERIAL CROSSING
WORK AREA 2 OF 2
PHASE 2 OF 4




ISSUE	DATE
1	03-12-19



CARPENTER RD.

E MARIPOSA RD.














CONTACT PROPERTY OWNER(S) 72 HOURS PRIOR TO START OF WORK.





FLAGGERS SHALL REMAIN IN COMMUNICATION VIA RADIO AT ALL TIMES.

FOR AERIAL CROSSING, ESTIMATED TIME OF COMPLETION IS 5 MINUTES.

LEGEND

	= PORTABLE FLASHING BEACON (P.F.B.)
	= TYPE III BARRICADE W/SIGN (5'H x 4'W)
	= TYPE II BARRICADE W/SIGN (3'H x 2'W)
	= 28" (11cm) TRAFFIC CONES W/ 13" (5cm) REFLECTIVE SLOTTES FOR DAY/NIGHT USE OR DELINEATORS IF DAY USE ONLY
	= TRAFFIC CONE WITH CLIP ON SIGN
	= TYPE I W SIGN
	= EXISTING SIGN
	= SIGNALIZED INTERSECTION
	= FLASHING ARROWBOARD
	= HIGH LEVEL WARNING DEVICE (FLAGTREE)
	= FLAGGER

TANSAT

	= TOW AWAY NO STOPPING ANY TIME
	= EXISTING DRIVEWAY
	= WORK ZONE (ACTIVITY AREA) LIMITS
	= DIRECTION OF TRAFFIC



MAINTAIN DRIVEWAY ACCESS AT ALL TIMES

PHASE 2 OF 4

TYPE OF CONSTRUCTION:
AERIAL CROSSING



JOB NUMBER: A01JGF6

PAGE: TC-3 OF TC-5 SCALE: 1:60
















E MARIPOSA RD. & CARPENTER RD.
-AERIAL PLACEMENT
WORK AREA 2 OF 2
PHASE 3 OF 4



ISSUE	DATE
1	03-12-19



LEGEND

	= PORTABLE FLASHING BEACON (P.F.B.)
	= TYPE III BARRICADE W/SIGN (5'H x 4'W)
	= TYPE II BARRICADE W/SIGN (3'H x 2'W)
	= 28\" data-bbox="105 255 125 275"/> (11cm) TRAFFIC CONES W/ 13\" data-bbox="105 255 125 275"/> (5cm) REFLECTIVE SLEEVE FOR DAY/NIGHT USE ONLY OR DELINEATORS IF DAY USE ONLY
	= TRAFFIC CONE WITH CLIP ON SIGN
	= TYPE I W/ SIGN
	= EXISTING SIGN
	= SIGNALIZED INTERSECTION
	= FLASHING ARROWBOARD
	= HIGH LEVEL WARNING DEVICE (FLAGTREE)
	= FLAGGER
	= TOW AWAY NO STOPPING ANY TIME
	= EXISTING DRIVEWAY
	= WORK ZONE (ACTIVITY AREA) LIMITS
	= DIRECTION OF TRAFFIC

MAINTAIN DRIVEWAY ACCESS AT ALL TIMES

PHASE 3 OF 4

TYPE OF CONSTRUCTION:
AERIAL PLACEMENT

JOB NUMBER: A01JGF6



PAGE: TC-4 OF TC-5

SCALE: 1:50

E MARIPOSA RD. & CARPENTER RD.
-AERIAL CROSSING
WORK AREA 2 OF 2
PHASE 4 OF 4



ISSUE	DATE
1	03-12-19



- LEGEND**
- PORTABLE FLASHING BEACON (P.F.B.)
 - TYPE III BARRICADE W/SIGN (5'H x 4'W)
 - TYPE II BARRICADE W/SIGN (3'H x 2'W)
 - 28" (11cm) TRAFFIC CONES W/ 13" (5cm) REFLECTIVE SLEEVE FOR DAY/NIGHT USE OR DELINEATORS IF DAY USE ONLY
 - TRAFFIC CONE WITH CLIP ON SIGN
 - TYPE I W/ SIGN
 - EXISTING SIGN
 - SIGNALIZED INTERSECTION
 - FLASHING ARROWBOARD
 - HIGH LEVEL WARNING DEVICE (FLAGTREE)
 - FLAGGER
 - TANSAT
 - TOW AWAY NO STOPPING ANY TIME
 - EXISTING DRIVEWAY
 - WORK ZONE (ACTIVITY AREA) LIMITS
 - DIRECTION OF TRAFFIC

MAINTAIN DRIVEWAY ACCESS AT ALL TIMES

PHASE 4 OF 4


TYPE OF CONSTRUCTION:
AERIAL CROSSING

JOB NUMBER: **A01JGF6**


PAGE: TC-5 OF TC-5

SCALE: 1:50

SIGN LEGEND



SYMBOL LEGEND



JOB LOCATION: 4550 E MARIPOSA RD.	WORK HOURS: FROM: _____ TO: _____
BEGIN CROSS STREET: E MUNFORD AVE.	END CROSS STREET: AUSTIN RD.
PERMIT NUMBER:	THOMAS GUIDE:
SCOPE OF WORK: POLE & GB PLACEMENT	
START DATE:	END DATE:
PERMIT WORK EXTENSIONS MUST BE OBTAINED BY THE END OF PERMIT DATE	

GENERAL TRAFFIC CONTROL NOTES:

1. THE CONTRACTOR IS RESPONSIBLE FOR PROMPTLY RESTORING THE ROAD BACK TO SATISFACTORY CONDITION WHICH INCLUDES, BUT IS NOT LIMITED TO, PAVING, STRIPING, MARKINGS, SIGNAGE, AND LOOP DETECTION. ALL PLANS SHALL BE IN ACCORDANCE WITH 2014 CAMUTCD.
2. THE AGENCY RESERVES THE RIGHT TO OBSERVE THESE TRAFFIC CONTROL PLANS IN OPERATION AND TO MAKE CHANGES AS FIELD CONDITIONS WARRANT.
3. TRENCHES SHALL BE BACKFILLED OR STEEL-PLATED DURING NON-WORK HOURS. STEEL PLATES SHALL HAVE AN ASPHALT RAMP ON ALL EDGES, SECURELY SUPPORTED SO THEY WON'T ROCK AND A SIGN POSTED NEAR THE PLATES IDENTIFYING THE CONTRACTOR'S NAME AND 24 HOUR EMERGENCY TELEPHONE NUMBER. ALL DIRT, DUST, AND DEBRIS SHALL BE REMOVED FROM THE STREET AT THE END OF EACH DAY AND AT THE END OF THE JOB. THE STREET SHALL BE KEPT IN A DRIVABLE CONDITION AT ALL TIMES.
4. ANY WORK THAT CREATES AN UNDUE SAFETY RISK OR THAT CREATES SEVERE CONGESTION WILL BE SHUT DOWN BY THE AGENCY.
5. A COPY OF ALL TRAFFIC REQUIREMENTS AND TRAFFIC CONTROL PLANS ISSUED BY THE AGENCY MUST BE KEPT ON THE JOB SITE.
6. APPROVAL OF THIS PLAN DOES NOT CONSTITUTE AN OFFICIAL PERMIT. CONTACT THE AGENCY FOR INFORMATION ON OBTAINING A PERMIT.
7. ALL TRAVEL LANES WILL TYPICALLY BE A MINIMUM OF 12 FEET WIDE, 14 FEET IF ADJACENT TO BIKE LANES, UNLESS OTHERWISE SPECIFICALLY APPROVED BY THE AGENCY.
8. FLASHING ARROW BOARDS AS REQUIRED BY THE AGENCY.
9. WARNING (W) SERIES SIGNS USED IN WORK ZONES SHALL BE BLACK ON AN ORANGE BACKGROUND.
10. CONES AND PYLONS SHALL HAVE YELLOW REFLECTORIZED SLEEVES WHEN PLACED ALONG THE CENTERLINE AND WHITE REFLECTORIZED SLEEVES ALONG THE OUTSIDE SHOULDER.
11. IF PARKING IS ALLOWED IN THE ADVANCE WORKING AREA, ADVANCE WARNING SIGNS SHALL BE MOUNTED ON HIGH LEVEL DEVICES.
12. THE CONTRACTOR SHALL POST TOW-AWAY/NO PARKING SIGNS SEVENTY-TWO (72) HOURS IN ADVANCE, WITH DAY OF WEEK, DATE, AND WORK HOURS NOTED, AND SHALL BAG PARKING METERS (WHERE APPLICABLE).
13. OPEN CUT WORK SHALL BE DONE IN __ PHASES.
14. WORKERS SHALL WEAR HARD HATS AND ORANGE VESTS AT ALL TIMES.
15. COUNTY TRANSIT DISTRICT SHALL BE NOTIFIED (5) WORKING DAYS PRIOR TO ANY WORK THAT AFFECTS BUS STOPS.
16. CONSTRUCTION SIGNS SHALL NOT OBSTRUCT SIGHT VISIBILITY AT DRIVEWAYS.
17. CONTRACTOR SHALL NOTIFY ALL LOCAL BUSINESS OWNERS/OCCUPANTS 72 HOURS IN ADVANCE PRIOR TO ANY CONSTRUCTION ADJACENT TO BUSINESSES.

ROAD TYPE	DISTANCE BETWEEN SIGNS**		
	A	B	C
URBAN - 25 MPH OR LESS***	100 FEET	100 FEET	100 FEET
URBAN - MORE THAN 25 MPH TO 40 MPH***	250 FEET	250 FEET	250 FEET
URBAN - MORE THAN 40 MPH***	350 FEET	350 FEET	350 FEET
RURAL	500 FEET	500 FEET	500 FEET
EXPRESSWAY/FREEWAY	1,000 FEET	1,500 FEET	2,640 FEET

** THE COLUMN HEADING A, B, AND C ARE THE DIMENSIONS SHOWN IN FIGURES 8H-1 THROUGH 8H-6. THE A DIMENSION IS THE DISTANCE FROM THE TRANSITION OR POINT OF RESTRICTION TO THE FIRST SIGN. THE B DIMENSION IS THE DISTANCE BETWEEN THE FIRST AND SECOND SIGNS. THE C DIMENSION IS THE DISTANCE BETWEEN THE SECOND AND THIRD SIGN. THE FIRST SIGN IS THE FIRST OF THE THREE-SIGN SERIES THAT IS CLOSEST TO TTC ZONE. THE "THIRD SIGN" IS THE SIGN THAT IS FURTHEST UPSTREAM FROM THE TTC ZONE.)

*** POSTED SPEED LIMIT, OR IF-PEAK 85TH-PERCENTILE SPEED PRIOR TO WORK STARTING, OR OTHER ANTICIPATED OPERATING SPEED IN MPH

**-TABLE 6C-2 2014 CALIFORNIA MUTCD-
STOPPING SIGHT DISTANCE AS A FUNCTION OF SPEED ON LEVEL ROAD
(USED AS SUGGESTED LONGITUDINAL BUFFER SPACE LENGTH OR
LOCATION FOR FLAGGER STATION)**

SPEED* (MPH)	DISTANCE (FT)
20	115
25	155
30	200
35	250
40	305
45	360
50	425
55	495
60	570
65	645
70	730
75	820

* POSTED SPEED, OFF-PEAK 85TH-PERCENTILE SPEED PRIOR TO WORK STARTING OR THE ANTICIPATED OPERATING SPEED IN MPH


-TABLE 6C-3 2014 CALIFORNIA MUTCD- -TAPER LENGTH CRITERIA FOR TEMPORARY TRAFFIC CONTROL ZONE-	
TYPE OF TAPER	TAPER LENGTH (L)*
MERGING TAPER	AT LEAST
SHIFTING TAPER	AT LEAST 0.5 L
SHOULDER TAPER	AT LEAST 0.3 L
ONE LANE, TWO-WAY TRAFFIC TAPER	SOFT MINIMUM, 100FT MAXIMUM
DOWNSTREAM TAPER	SOFT MINIMUM, 100FT MAXIMUM

-TABLE 6C-4 2014 CALIFORNIA MUTCD- -FORMULAS FOR DETERMINING TAPER LENGTH-	
SPEED LIMIT (S)	TAPER LENGTH (L) FEET
40 MPH OR LESS	$L = \frac{WS}{55}$
45 MPH OR MORE	$L = WS$


WHERE: L= TAPER LENGTH IN METERS (FEET)
W= WIDTH OF OFFSET IN METERS (FEET)
S= POSTED SPEED LIMIT, OR OFF-PEAK
85TH-PERCENTILE SPEED PRIOR TO WORK
STARTING, OR THE ANTICIPATED OPERATING
SPEED IN KM/H (MPH)

COUNTY OF: SAN JOAQUIN

TRAFFIC CONTROL PLAN

PLANS ACCEPTED BY:	 CHC Consulting 1845 W. Orangewood Ave., Suite 300, Orange, CA 92668 (949) 250-0004 / FAX (949) 250-0006
DATE	
R.C.E.	
EXP. DATE	PLANS PREPARED BY: NAME: <u>AMANPREET SINGH</u> PHONE: <u>(949) 250-0004</u> DATE: <u>03-14-19</u> REVISION DATE: <u>N/A</u>


JOB NUMBER A01JGF6
SCALE: N/A
PAGE: COVER SHEET

The logo for at&t California, featuring a blue and white striped globe icon to the left of the text "at&t" in a bold, sans-serif font, with "California" in a smaller, italicized font below it.


4550 E MARIPOSA RD.
MARIPOSA RD. & CARPENTER RD.
POLE & GB PLACEMENT
WORK AREA 1 OF 2



ISSUE	DATE
1	03-14-19



LOCATION MAP



LEGEND

- * = PORTABLE FLASHING BEACON (P.F.B.)
- ☒ = TYPE III BARRICADE W/SIGN (5'H x 4'W)
- ☒ = TYPE II BARRICADE W/SIGN (3'H x 2'W)
- = 28" (11cm) TRAFFIC CONES W/ 13" (5cm) REFLECTIVE SLEEVE FOR DAY/NIGHT USE OR DELINEATORS IF DAY USE ONLY
- ☒ = TRAFFIC CONE WITH CLIP ON SIGN
- ☒ = TYPE I W/ SIGN
- ☒ = EXISTING SIGN
- Ⓢ = SIGNALIZED INTERSECTION
- ☒ = FLASHING ARROWBOARD
- ☒ = HIGH LEVEL WARNING DEVICE (FLAGTREE)
- ☒ = FLAGGER
- TANSAT = TOW AWAY NO STOPPING ANY TIME
- ☒ = EXISTING DRIVEWAY
- ☒ = WORK ZONE (ACTIVITY AREA) LIMITS
- = DIRECTION OF TRAFFIC



MAINTAIN DRIVEWAY ACCESS
AT ALL TIMES

PHASE 1 OF 1

TYPE OF CONSTRUCTION:
POLE & GB PLACEMENT
JOB NUMBER: **A01JGF6**
PAGE: TC-1 OF TC-2 SCALE: 1:30

4801 CARPENTER RD.
CARPENTER RD. & MARIPOSA RD.
POLE & GB PLACEMENT
WORK AREA 2 OF 2




ISSUE	DATE
1	03-14-19


CONTACT PROPERTY OWNER(S) 72
HOURS PRIOR TO START OF WORK.

POLE IS +/- 365' EAST OF THE
C/L OF E MARIPOSA RD.

4801 CARPENTER RD.



LOCATION MAP



LEGEND

- * = PORTABLE FLASHING BEACON (P.F.B.)
- ☒ = TYPE III BARRICADE W/SIGN (6'H x 4'W)
- ☒ = TYPE II BARRICADE W/SIGN (3'H x 2'W)
- = 28" (11cm) TRAFFIC CONES W/ 13" (5cm) REFLECTIVE SLEEVE FOR DAY/NIGHT USE OR DELINEATORS IF DAY USE ONLY
- = TRAFFIC CONE WITH CLIP ON SIGN
- ☐ = TYPE I W/ SIGN
- ☐ = EXISTING SIGN
- Ⓢ = SIGNALIZED INTERSECTION
- ☐ = FLASHING ARROWBOARD
- ☐ = HIGH LEVEL WARNING DEVICE (FLAGTREE)
- ☐ = FLAGGER
- TANSAT = TOW AWAY NO STOPPING ANY TIME
- ☐ = EXISTING DRIVEWAY
- ▨ = WORK ZONE (ACTIVITY AREA) LIMITS
- = DIRECTION OF TRAFFIC



MAINTAIN DRIVEWAY ACCESS
AT ALL TIMES

PHASE 1 OF 1

TYPE OF CONSTRUCTION:
POLE & GB PLACEMENT
JOB NUMBER: **A01JGF6**
PAGE: TC-2 OF TC-2 SCALE: 1:30